

Bioscan
Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
1.1 Product identifier

Product name : Bioscan

Product code : 109841E

Use of the Substance/Mixture : Sanitary cleaner

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Sanitary cleaner. Manual process
Sanitary cleaner. Spray and wipe manual process

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : +441618841235
+32-(0)3-575-5555 Trans-European

Poison Information Centre telephone number : For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 30.12.2022
Version : 2.1

Section: 2. HAZARDS IDENTIFICATION
2.1 Classification of the substance or mixture
Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1B	H314
Serious eye damage, Category 1	H318
Acute aquatic toxicity, Category 1	H400
Chronic aquatic toxicity, Category 2	H411

Bioscan**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.
 H400 Very toxic to aquatic life.
 H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH071 Corrosive to the respiratory tract.

Precautionary Statements : **Prevention:**
 P260 Do not breathe vapours.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Alkylamine ethoxylates

Trimethyl(tallowalkyl)ammonium chloride

Additional Labelling:

Special labelling of certain mixtures : Contains: terpinolene, oils, lemon, Limonene, solvents /additives, May produce an allergic reaction.

2.3 Other hazards

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Alkylamine ethoxylates	25307-17-9 246-807-3 01-2119510876-35	Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410	>= 5 - < 10

Bioscan

		M = 10 M(Chronic) = 1	
Trimethyl(tallowalkyl)amm onium chloride	8030-78-2 232-447-4	Acute toxicity Category 4; H302 Acute aquatic toxicity Category 1; H400 Serious eye damage/eye irritation Category 1; H318 Skin corrosion/irritation Category 1B; H314	>= 1 - < 2.5
citric acid, monohydrate	5949-29-1 201-069-1 01-2119457026-42	Eye irritation Category 2; H319	>= 1 - < 2.5
Isopropyl Alcohol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 1 - < 2.5
terpinolene	586-62-9 209-578-0 01-2119982325-32	Flammable liquids Category 3; H226 Skin sensitization Sub-category 1B; H317 Aspiration hazard Category 1; H304 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410	>= 0.25 - < 0.5
oils, lemon	8008-56-8	Flammable liquids Category 3; H226 Skin irritation Category 2; H315 Eye irritation Category 2; H319 Skin sensitization Sub-category 1B; H317 Aspiration hazard Category 1; H304 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410	>= 0.25 - < 0.5
Limonene	5989-27-5 227-813-5 01-2119529223-47	Nota C Flammable liquids Category 3; H226 Skin irritation Category 2; H315 Skin sensitization Category 1; H317 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410 Aspiration hazard Category 1; H304 M = 1 M(Chronic) = 1	>= 0.1 - < 0.25
solvents /additives	1330-16-1 215-533-6	Skin irritation Category 2; H315 Skin sensitization Sub-category 1A; H317 Aspiration hazard Category 1; H304 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410	>= 0.025 - < 0.1

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Bioscan

- | | |
|--------------|---|
| If swallowed | : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately. |
| If inhaled | : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur. |

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- | | |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | : None known. |

5.2 Special hazards arising from the substance or mixture

- | | |
|--------------------------------------|--|
| Specific hazards during firefighting | : Not flammable or combustible. |
| Hazardous combustion products | : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NOx)
Hydrogen chloride |

5.3 Advice for firefighters

- | | |
|---|--|
| Special protective equipment for firefighters | : Use personal protective equipment. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes. |

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

- | | |
|------------------------------------|--|
| Advice for non-emergency personnel | : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8. |
|------------------------------------|--|

Bioscan

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 40 °C

7.3 Specific end uses

Specific use(s) : Sanitary cleaner. Manual process
Sanitary cleaner. Spray and wipe manual process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Bioscan**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Isopropyl Alcohol	67-63-0	TWA	400 ppm 999 mg/m ³	UKCOSSTD
		STEL	500 ppm 1,250 mg/m ³	UKCOSSTD

DNEL

Isopropyl Alcohol	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects 888 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 500 mg/m³ End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects 319 mg/kg End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m³ End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects 26 mg/kg
-------------------	---	---

PNEC

Isopropyl Alcohol	:	Fresh water Value: 140.9 mg/l Marine water Value: 140.9 mg/l Intermittent use/release Value: 140.9 mg/l Fresh water Value: 552 mg/kg Marine sediment Value: 552 mg/kg Soil Value: 28 mg/kg Sewage treatment plant Value: 2251 mg/l Oral
-------------------	---	---

Bioscan

Value: 160 mg/kg

8.2 Exposure controls**Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advice).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes

Respiratory protection (EN 143, 14387) : When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:A

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

Appearance : liquid
Colour : light yellow
Odour : citrus
pH : 4.5 - 5.5, 100 %
Flash point : Not applicable.

Bioscan

Odour Threshold	: Not applicable and/or not determined for the mixture
Melting point/freezing point	: Not applicable and/or not determined for the mixture
Initial boiling point and boiling range	: > 100 °C
Evaporation rate	: Not applicable and/or not determined for the mixture
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture
Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 0.99 - 1.015
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: 220.396 mm ² /s (40 °C)
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: Yes

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Bioscan

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides
nitrogen oxides (NO_x)
Hydrogen chloride

Section: 11. TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects**

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	: There is no data available for this product.
Acute dermal toxicity	: There is no data available for this product.
Skin corrosion/irritation	: There is no data available for this product.
Serious eye damage/eye irritation	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.
Teratogenicity	: There is no data available for this product.
STOT - single exposure	: There is no data available for this product.
STOT - repeated exposure	: There is no data available for this product.
Aspiration toxicity	: There is no data available for this product.

Components

Acute oral toxicity	: Alkylamine ethoxylates LD50 rat: 1,260 mg/kg
	Trimethyl(tallowalkyl)ammonium chloride LD50 rat: 1,260 mg/kg
	citric acid, monohydrate LD50 rat: 11,700 mg/kg
	Isopropyl Alcohol LD50 rat: 5,840 mg/kg
	terpinolene LD50 rat: 3,740 mg/kg
	oils, lemon LD50 rat: 2,840 mg/kg
	Limonene LD50 rat: 4,400 mg/kg

Bioscan

Components

Acute inhalation toxicity : Isopropyl Alcohol 4 h LC50 rat: > 30 mg/l
Test atmosphere: vapour

Components

Acute dermal toxicity : Trimethyl(tallowalkyl)ammonium chloride LD50 rabbit: > 2,930 mg/kg

citric acid, monohydrate LD50 rat: > 2,000 mg/kg

Isopropyl Alcohol LD50 rabbit: 12,870 mg/kg

Limonene LD50 rabbit: > 5,000 mg/kg

Potential Health Effects

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Environmental Effects : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : Alkylamine ethoxylates 96 h LC50 Danio rerio (zebra fish): 0.1 mg/l

citric acid, monohydrate 96 h LC50 Fish: > 100 mg/l

Isopropyl Alcohol 96 h LC50 Pimephales promelas (fathead

Bioscan

minnow): 9,640 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : Alkylamine ethoxylates 48 h EC50 Daphnia magna (Water flea): 0.043 mg/l

Isopropyl Alcohol LC50 Daphnia magna (Water flea): > 10,000 mg/l

terpinolene 48 h EC50: 0.634 mg/l

Limonene 48 h EC50 Daphnia magna (Water flea): 0.307 mg/l

Components

Toxicity to algae : Alkylamine ethoxylates 72 h EC50 Pseudokirchneriella subcapitata (microalgae): 0.0538 mg/l

Limonene 72 h EC50 Pseudokirchneriella subcapitata (algae): 0.32 mg/l

12.2 Persistence and degradability

Product

no data available

Components

Biodegradability : Alkylamine ethoxylates Result: Readily biodegradable.

Trimethyl(tallowalkyl)ammonium chloride Result: Biodegradable

citric acid, monohydrate Result: Readily biodegradable.

Isopropyl Alcohol Result: Readily biodegradable.

terpinolene Result: Readily biodegradable.

Limonene Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Bioscan**12.6 Other adverse effects**

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

- | | | |
|-----------------------------------|---|---|
| Product | : | Do not contaminate storm water drains, natural waterways or soil with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility. |
| Contaminated packaging | : | Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations. |
| Guidance for Waste Code selection | : | Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations. |

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- | | | |
|-----------------------------------|---|---|
| 14.1 UN number | : | 3265 |
| 14.2 UN proper shipping name | : | CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
(ethanol, 2,2'-(9-octadecenylimino)bis-) |
| 14.3 Transport hazard class(es) | : | 8 |
| 14.4 Packing group | : | III |
| 14.5 Environmental hazards | : | Yes |
| 14.6 Special precautions for user | : | None |

Air transport (IATA)

- | | | |
|---------------------------------|---|---|
| 14.1 UN number | : | 3265 |
| 14.2 UN proper shipping name | : | Corrosive liquid, acidic, organic, n.o.s.
(ethanol, 2,2'-(9-octadecenylimino)bis-) |
| 14.3 Transport hazard class(es) | : | 8 |
| 14.4 Packing group | : | III |

Bioscan

14.5 Environmental hazards : Yes

14.6 Special precautions for user : None

Sea transport (IMDG/IMO)

14.1 UN number : 3265

14.2 UN proper shipping name : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

(ethanol, 2,2'-(9-octadecenylimino)bis-)

14.3 Transport hazard class(es) : 8

14.4 Packing group : III

14.5 Environmental hazards : Yes

14.6 Special precautions for user : None

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Section: 15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**according to Detergents Regulation EC 648/2004 : Other constituents: Perfumes
Preservation agents:
1,2-benzisothiazol-3(2H)-oneAllergens:
LimoneneCitralLinaloolSeveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : ENVIRONMENTAL HAZARDS E1
Lower tier : 100 t
Upper tier : 200 t

Candidate List of Substances of Very High Concern for Authorisation : Not applicable.

National Regulations**Take note of Dir 94/33/EC on the protection of young people at work.**Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.
The Control of Substances Hazardous to Health Regulations.
Health and Safety at Work Act.**15.2 Chemical Safety Assessment**

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
----------------	---------------

Bioscan

Skin corrosion 1B, H314	Calculation method
Serious eye damage 1, H318	Calculation method
Acute aquatic toxicity 1, H400	Calculation method
Chronic aquatic toxicity 2, H411	Calculation method

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

Bioscan

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios**Exposure Scenario: Sanitary cleaner. Manual process**

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Bioscan

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Exposure Scenario: Sanitary cleaner. Spray and wipe manual process

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

Bioscan

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC11** Non industrial spraying

Exposure duration : 60 min

Operational conditions and
risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8