

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

JohnsonDiversey

JohnsonDiversey UK Limited

Weston Favell Centre Northampton NN3 8PD Tel 01604 405311 Fax 01604 406809 Emergency Call 0800 052 0185

N02849

Clearance Code
R55164

TASKI TAPI DEFOAM C1g
Antifoam

Product Code
MSDS4746

TO :

2. COMPOSITION / INFORMATION ON INGREDIENTS

CAS No	EINECS No			
67-63-0	200-661-7	Propan-2-ol (WEL)	Xi, F: R11-36-67	(>30%)

Full text of R-phrases is given in section 16.

3. HAZARDS IDENTIFICATION

Irritant - irritating to eyes.
Highly flammable.
Vapours may cause drowsiness and dizziness.
This product contains a material with an WEL published in HSE document EH40.

4. FIRST AID MEASURES

Eyes : Rinse immediately with plenty of water, holding the eyelids open and seek medical advice.
Inhalation : Remove from source of exposure.
Skin : Wash thoroughly with soap and water.
Ingestion : Remove product from mouth, give the casualty a small quantity of water to drink and seek medical advice. Do not induce vomiting.

5. FIRE FIGHTING MEASURES

HIGHLY FLAMMABLE - In the event of a fire use water spray, alcohol resistant foam, carbon dioxide or dry powder extinguishers. May evolve toxic fumes if involved in a fire. Firefighters should wear self contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Wear suitable gloves and eye/face protection. Turn off all sources of ignition and ventilate the area. Hose away with plenty of water diluting to at least 0.5% w/v (5 g/litre) unless this would contaminate a water course or vegetation, in which case either collect, dilute as earlier and pour down wastewater drain (foul sewer) or absorb onto dry sand or similar material and dispose of to a licensed waste management company.

7. HANDLING & STORAGE

Avoid contact with eyes. Always ensure good ventilation when using this product. Do not use near naked flames, incandescent surfaces or other sources of ignition. Do not mix with any other chemicals other than as advised by your JohnsonDiversey representative.
Store upright in original containers in a cool place. Keep tightly closed. This product is not classified as flammable by HS(G)51 (Storage of Flammable Liquids in Containers).

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Hand : For prolonged contact, the use of gloves resistant to solvents is recommended
Eyes : Personal protection is not normally required unless a risk assessment indicates the need for it.
Skin : Personal protection is not normally required unless a risk assessment indicates the need for it.
Respiration : Personal protection is not normally required unless a risk assessment indicates the need for it.

WEL : Propan-2-ol, (Isopropanol), (Isopropyl Alcohol)
W.E.L. 1250 mg/cu.m 15 min ref time
W.E.L. 999 mg/cu.m 8 hour TWA.

ref. HSE publication EH40

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance :	Colourless liquid	Odour :	Characteristic
Flammability :	Flammable	Solubility :	Miscible with water
Boiling Point :	<100°C	Flash Point :	13°C Pensky M. cc
Density :	0.80 g/ml	Explosive properties :	Product not explosive

10. STABILITY & REACTIVITY

Provided the product is stored in accordance with the approved guidelines there are no known hazardous decomposition products.

11. TOXICOLOGICAL INFORMATION

Eyes :	Irritant
Skin :	Unlikely to be irritant in normal use.
Inhalation :	Irritant
Ingestion :	Irritant

12. ECOLOGICAL INFORMATION

When used for its intended purpose this product should not cause adverse effects in the environment.

13. DISPOSAL CONSIDERATIONS

This product does not contain any prescribed substance under the Environmental Protection Act (Prescribed Processes and Substances) Regulations 1991 but is classified as special waste under the Control of Substances (Special Waste) Regulations 1996. For small quantities wear suitable gloves and eye/face protection. Dilute with water to at least 0.5% w/v (5 g/litre) and pour down a wastewater drain (foul sewer). Rinse out containers at least twice and recycle if facilities exist or dispose of as commercial waste. For larger quantities contact a licensed waste management company.

European waste catalogue 16 03 05 Organic wastes containing dangerous substances.

14. TRANSPORT INFORMATION

EEC Regulation :	F, FLAMMABLE, Isopropanol solution, UN1219, Hazchem 2YE
IMDG/UN :	Isopropanol solution, UN1219, Class 3.2, PG II
RID/ADR :	Class 3, Item 3(b)
ICAO/IATA :	Passenger Aircraft: 305, Y305 Cargo Aircraft: 307

15. REGULATORY INFORMATION

Hazard symbol :	F, Xi, HIGHLY FLAMMABLE & IRRITANT, Contains Isopropanol
Risk phrases :	R11 Highly flammable. R36 Irritating to eyes. R67 Vapours may cause drowsiness and dizziness.
Safety phrases :	S9 Keep container in a well-ventilated place. S16 Keep away from sources of ignition - No smoking. S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. This product contains a material with an WEL published in HSE document EH40.

16. OTHER INFORMATION

Handle and apply only as recommended, for full information see product information sheet.

Internal Reference:- MSDS4746-02 (29-Apr-2005)
BC.CA.Af01 (01-Jul-1994)

Text of risk phrases associated with ingredients listed in section 2.

R11 Highly flammable.
R36 Irritating to eyes.
R67 Vapours may cause drowsiness and dizziness.
