

N04438

REVISION DATE: 10th October 2005

Product No.:OPTK10



HOLCHEM

SAFETY DATA SHEET STAINLESS STEEL POLISH

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME STAINLESS STEEL POLISH
PRODUCT NO. OPTK10
SUPPLIER Holchem Laboratories Limited
Premier House
175 Grane Road, Haslingden
Rossendale, Lancashire. BB4 5ER
01706 222288
01706 221550

EMERGENCY TELEPHONE Medical Emergencies Only: NPIS Tel. 0207 635 9191 Fax. 0207 635 1053 Holchem (Office Hours): Tel. 01706 222288 Fax. 01706 221550 Holchem (Outside Office Hours): Tel. 07050 265597

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ALIPHATIC HYDROCARBON	265-149-8	64742-47-8	30-60%	Xn;R65.

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Harmful: may cause lung damage if swallowed.

CLASSIFICATION Xn;R65.

4 FIRST-AID MEASURES

INHALATION

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. If breathing stops, provide artificial respiration. Get medical attention.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Place unconscious person on the side in the recovery position and ensure breathing can take place. Get medical attention.

SKIN CONTACT

Immediately remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials. DO NOT use water if avoidable.

SPECIAL FIRE FIGHTING PROCEDURES

Use air respirator if substance is involved in a fire.

UNUSUAL FIRE & EXPLOSION HAZARDS

Vapours may ignite.

SPECIFIC HAZARDS

Oxides of: Carbon.

6 ACCIDENTAL RELEASE MEASURES

STAINLESS STEEL POLISH

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Should be prevented from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Inform Authorities if large amounts are involved. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Wear full protective clothing for prolonged exposure and/or high concentrations. Read and follow manufacturer's recommendations.

STORAGE PRECAUTIONS

Keep containers tightly closed. Keep away from heat, sparks and open flame.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Rubber, neoprene or PVC.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear suitable protective clothing as protection against splashing or contamination.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear		
COLOUR	Colourless		
ODOUR	Kerosene.		
SOLUBILITY	Immiscible with water		
MELTING POINT (°C)	< 0	RELATIVE DENSITY	0.82 @ 20 °c
FLASH POINT (°C)	83 CC (Closed cup).		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS

Oxides of: Carbon.

11 TOXICOLOGICAL INFORMATION

INHALATION

Vapour may irritate respiratory system or lungs.

INGESTION

Harmful: may cause lung damage if swallowed.

STAINLESS STEEL POLISH

SKIN CONTACT

Irritating to skin.

EYE CONTACT

Irritating to eyes.

12 ECOLOGICAL INFORMATION

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

No transport warning sign required.

ADR CLASS

Not classified for transportation. **MARINE POLLUTANT**

No.

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS

ALIPHATIC HYDROCARBON

RISK PHRASES

R65

Harmful: may cause lung damage if swallowed.

SAFETY PHRASES

S60

This material and its container must be disposed of as hazardous waste.

S62

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

DETERGENT LABELLING

> 30%

Aliphatic hydrocarbons

16 OTHER INFORMATION

REVISION DATE

10th October 2005

RISK PHRASES IN FULL

R65

Harmful: may cause lung damage if swallowed.