

**Neomax BMR****Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : Neomax BMR

Product code : 115801E

Use of the  
Substance/Mixture : Floor Stripper

Substance type: : Mixture

**For professional users only.**

Product dilution information : No dilution information provided.

**1.2 Relevant identified uses of the substance or mixture and uses advised against**Identified uses : Floor stripper. Manual process  
Floor stripper. Semi-Automatic processRecommended restrictions  
on use : Reserved for industrial and professional use.**1.3 Details of the supplier of the safety data sheet**Company : Ecolab Ltd.  
PO Box 11; Winnington Avenue  
Northwich, Cheshire, United Kingdom CW8 4DX  
+ 44 (0)1606 74488  
ccs@ecolab.com**1.4 Emergency telephone number**Emergency telephone  
number : +441618841235  
+32-(0)3-575-5555 Trans-EuropeanPoison Information Centre  
telephone number : For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 18.10.2023

Version : 3.2

**Section: 2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

|                                                               |      |
|---------------------------------------------------------------|------|
| Skin corrosion, Category 1                                    | H314 |
| Serious eye damage, Category 1                                | H318 |
| Skin sensitization, Category 1                                | H317 |
| Specific target organ toxicity - single exposure, Category 3, | H335 |

**Neomax BMR**

Respiratory system  
Chronic aquatic toxicity, Category 2

H411

**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH071 Corrosive to the respiratory tract.

Precautionary Statements : **Prevention:**  
P261 Avoid breathing vapours.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

monoethanolamine  
Isotridecanol, ethoxylated  
Limonene

**2.3 Other hazards**

None known.

**Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS****3.2 Mixtures****Hazardous components**

| Chemical Name             | CAS-No.<br>EC-No.<br>REACH No.            | Classification<br>REGULATION (EC) No 1272/2008                                                                                                                                             | Concentration<br>: [%] |
|---------------------------|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| 2-(2-butoxyethoxy)ethanol | 112-34-5<br>203-961-6<br>01-2119475104-44 | Eye irritation Category 2; H319                                                                                                                                                            | >= 20 - < 25           |
| monoethanolamine          | 141-43-5<br>205-483-3<br>01-2119486455-28 | Acute toxicity Category 4; H302<br>Acute toxicity Category 4; H332<br>Acute toxicity Category 4; H312<br>Skin corrosion Sub-category 1B; H314<br>Chronic aquatic toxicity Category 3; H412 | >= 5 - < 10            |

**Neomax BMR**

|                            |                                             |                                                                                                                                                                                                                                                                                   |              |
|----------------------------|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
|                            |                                             | Specific target organ toxicity - single exposure Category 3; H335<br><br>Specific target organ toxicity - single exposure Category 3<br>H335 5 - 100 %                                                                                                                            |              |
| Isotridecanol, ethoxylated | 69011-36-5<br>500-241-6<br>01-2119976362-32 | Acute toxicity Category 4; H302<br>Skin irritation Category 2; H315<br>Serious eye damage Category 1; H318<br>Chronic aquatic toxicity Category 3; H412                                                                                                                           | >= 3 - < 5   |
| Limonene                   | 5989-27-5<br>227-813-5<br>01-2119529223-47  | Nota C Flammable liquids Category 3; H226<br>Skin irritation Category 2; H315<br>Skin sensitization Category 1; H317<br>Acute aquatic toxicity Category 1; H400<br>Chronic aquatic toxicity Category 1; H410<br>Aspiration hazard Category 1; H304<br><br>M = 1<br>M(Chronic) = 1 | >= 2.5 - < 5 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

**Section: 4. FIRST AID MEASURES****4.1 Description of first aid measures**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

**4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

**4.3 Indication of immediate medical attention and special treatment needed**

- Treatment : Treat symptomatically.

**Section: 5. FIREFIGHTING MEASURES****5.1 Extinguishing media**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.

**Neomax BMR**

**5.2 Special hazards arising from the substance or mixture**

- |                                      |                                                                                                                                         |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Specific hazards during firefighting | : Fire Hazard<br>Keep away from heat and sources of ignition.<br>Flash back possible over considerable distance.                        |
| Hazardous combustion products        | : Depending on combustion properties, decomposition products may include following materials:<br>Carbon oxides<br>nitrogen oxides (NOx) |

**5.3 Advice for firefighters**

- |                                               |                                                                                                                                                                                                                                                                                    |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Special protective equipment for firefighters | : Use personal protective equipment.                                                                                                                                                                                                                                               |
| Further information                           | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes. |

**Section: 6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

- |                                    |                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advice for non-emergency personnel | : Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8. |
| Advice for emergency responders    | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.                                                                                                                                                                                                                                                             |

**6.2 Environmental precautions**

- |                           |                                                            |
|---------------------------|------------------------------------------------------------|
| Environmental precautions | : Do not allow contact with soil, surface or ground water. |
|---------------------------|------------------------------------------------------------|

**6.3 Methods and materials for containment and cleaning up**

- |                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Methods for cleaning up | : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**6.4 Reference to other sections**

See Section 1 for emergency contact information.  
For personal protection see section 8.  
See Section 13 for additional waste treatment information.

**Neomax BMR****Section: 7. HANDLING AND STORAGE****7.1 Precautions for safe handling**

- Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Keep away from heat and sources of ignition. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
- Storage temperature : 0 °C to 30 °C

**7.3 Specific end uses**

- Specific use(s) : Floor stripper. Manual process  
Floor stripper. Semi-Automatic process

**Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters****Occupational Exposure Limits**

| Components                | CAS-No.  | Value type (Form of exposure)                                                                                                                           | Control parameters                | Basis    |
|---------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|----------|
| 2-(2-butoxyethoxy)ethanol | 112-34-5 | TWA                                                                                                                                                     | 10 ppm<br>67.5 mg/m <sup>3</sup>  | UKCOSSTD |
|                           |          | STEL                                                                                                                                                    | 15 ppm<br>101.2 mg/m <sup>3</sup> | UKCOSSTD |
| monoethanolamine          | 141-43-5 | TWA                                                                                                                                                     | 1 ppm<br>2.5 mg/m <sup>3</sup>    | UKCOSSTD |
| Further information       | Sk       | Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                                   |          |
|                           |          | STEL                                                                                                                                                    | 3 ppm<br>7.6 mg/m <sup>3</sup>    | UKCOSSTD |
| Further information       | Sk       | Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                                   |          |

**DNEL**

|                           |   |                                                                                                                                                           |
|---------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2-(2-butoxyethoxy)ethanol | : | End Use: Workers<br>Exposure routes: Inhalation<br>Potential health effects: Short-term - local<br>Value: 101.2 mg/m <sup>3</sup><br><br>End Use: Workers |
|---------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------|

**Neomax BMR**

|  |                                                                                                                                                                                                                                                                                                                                                                    |
|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Exposure routes: Dermal<br>Potential health effects: Long-term systemic effects<br>Value: 20 mg/kg<br><br>End Use: Workers<br>Exposure routes: Inhalation<br>Potential health effects: Long-term systemic effects<br>Value: 67.5 mg/m3<br><br>End Use: Workers<br>Exposure routes: Inhalation<br>Potential health effects: Short-term - local<br>Value: 67.5 mg/m3 |
|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**PNEC**

|                           |                                                                                                                                                                                                                                                                               |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2-(2-butoxyethoxy)ethanol | :<br>Fresh water<br>Value: 1 mg/l<br><br>Marine water<br>Value: 0.1 mg/l<br><br>Intermittent use/release<br>Value: 3.9 mg/l<br><br>Sewage treatment plant<br>Value: 200 mg/l<br><br>Sediment<br>Value: 4 mg/kg<br><br>Soil<br>Value: 0.4 mg/kg<br><br>Oral<br>Value: 56 mg/kg |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**8.2 Exposure controls****Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

**Individual protection measures**

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles  
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection

**Neomax BMR**

Gloves  
 Nitrile rubber  
 butyl-rubber  
 Breakthrough time: 1 – 4 hours  
 Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).  
 Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes

Respiratory protection (EN 143, 14387) : When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:A-P

**Environmental exposure controls**

General advice : Consider the provision of containment around storage vessels.

**Section: 9. PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

|                                         |                                                        |
|-----------------------------------------|--------------------------------------------------------|
| Appearance                              | : liquid                                               |
| Colour                                  | : orange                                               |
| Odour                                   | : citrus                                               |
| pH                                      | : 11.3 - 12.5, 100 %                                   |
| Flash point                             | : 66 °C open cup, Does not sustain combustion.         |
| Odour Threshold                         | : Not applicable and/or not determined for the mixture |
| Melting point/freezing point            | : Not applicable and/or not determined for the mixture |
| Initial boiling point and boiling range | : Not applicable and/or not determined for the mixture |
| Evaporation rate                        | : Not applicable and/or not determined for the mixture |
| Flammability (solid, gas)               | : Not applicable and/or not determined for the mixture |
| Upper explosion limit                   | : Not applicable and/or not determined for the mixture |
| Lower explosion limit                   | : Not applicable and/or not determined for the mixture |
| Vapour pressure                         | : Not applicable and/or not determined for the mixture |
| Relative vapour density                 | : Not applicable and/or not determined for the mixture |
| Relative density                        | : 0.99 - 1.0                                           |
| Water solubility                        | : soluble                                              |
| Solubility in other solvents            | : Not applicable and/or not determined for the mixture |
| Partition coefficient: n-octanol/water  | : Not applicable and/or not determined for the mixture |
| Auto-ignition temperature               | : Not applicable and/or not determined for the mixture |

**Neomax BMR**

Thermal decomposition : Not applicable and/or not determined for the mixture  
Viscosity, kinematic : Not applicable and/or not determined for the mixture  
Explosive properties : Not applicable and/or not determined for the mixture  
Oxidizing properties : The substance or mixture is not classified as oxidizing.

**9.2 Other information**

Not applicable and/or not determined for the mixture

**Section: 10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

No dangerous reaction known under conditions of normal use.

**10.4 Conditions to avoid**

Heat, flames and sparks.

**10.5 Incompatible materials**

None known.

**10.6 Hazardous decomposition products**

Depending on combustion properties, decomposition products may include following materials:  
Carbon oxides  
nitrogen oxides (NOx)

**Section: 11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

**Product**

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg  
Acute inhalation toxicity : 4 h Acute toxicity estimate : > 5 mg/l  
Test atmosphere: dust/mist  
Acute dermal toxicity : Acute toxicity estimate : > 2,000 mg/kg  
Skin corrosion/irritation : There is no data available for this product.



**Neomax BMR**

Serious eye damage/eye irritation : There is no data available for this product.

Respiratory or skin sensitization : There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

**Components**

Acute oral toxicity : 2-(2-butoxyethoxy)ethanol LD50 rat: 3,306 mg/kg

monoethanolamine LD50 rat: 1,089 mg/kg

Isotridecanol, ethoxylated LD50 rat: 800 mg/kg

Test substance: Information given is based on data obtained from similar substances.

Limonene LD50 rat: 4,400 mg/kg

**Components**

Acute inhalation toxicity : monoethanolamine 4 h LC50 rat: > 1.6 mg/l  
Test atmosphere: dust/mist

**Components**

Acute dermal toxicity : 2-(2-butoxyethoxy)ethanol LD50 rabbit: 2,764 mg/kg

monoethanolamine LD50 rabbit: 1,025 mg/kg

Isotridecanol, ethoxylated LD50 rat: 2,150 mg/kg

Test substance: Information given is based on data obtained from similar substances.

Limonene LD50 rabbit: > 5,000 mg/kg

**Potential Health Effects**

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns. May cause allergic skin reaction.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

**Neomax BMR**

Chronic Exposure : Health injuries are not known or expected under normal use.

**Experience with human exposure**

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Irritation, Corrosion, Allergic reactions

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

**Section: 12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

Environmental Effects : Toxic to aquatic life with long lasting effects.

**Product**

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

**Components**

Toxicity to fish : 2-(2-butoxyethoxy)ethanol 96 h LC50 Fish: 1,300 mg/l

Isotridecanol, ethoxylated 96 h LC50 Fish: 20.13 mg/l  
Test substance: Information given is based on data obtained from similar substances.

**Components**

Toxicity to daphnia and other aquatic invertebrates : monoethanolamine 48 h LC50 Daphnia magna (Water flea): 65 mg/l

Isotridecanol, ethoxylated 48 h EC50 Daphnia magna (Water flea): 5.33 mg/l  
Test substance: Information given is based on data obtained from similar substances.

Limonene 48 h EC50 Daphnia magna (Water flea): 0.307 mg/l

**Components**

Toxicity to algae : Limonene 72 h EC50 Pseudokirchneriella subcapitata (algae): 0.32 mg/l

**12.2 Persistence and degradability**

**Product**

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

**Components**

**Neomax BMR**

Biodegradability : 2-(2-butoxyethoxy)ethanolResult: Readily biodegradable.  
monoethanolamineResult: Readily biodegradable.  
Isotridecanol, ethoxylatedResult: Readily biodegradable.  
LimoneneResult: Readily biodegradable.

**12.3 Bioaccumulative potential**

no data available

**12.4 Mobility in soil**

no data available

**12.5 Results of PBT and vPvB assessment**

**Product**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects**

no data available

**Section: 13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with the European Directives on waste and hazardous waste.Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

**13.1 Waste treatment methods**

Product : Do not contaminate storm water drains, natural waterways or soil with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

**Section: 14. TRANSPORT INFORMATION**

**Neomax BMR**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

**Land transport (ADR/ADN/RID)**

- 14.1 UN number : 3267  
14.2 UN proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.  
(monoethanolamine, Limonene)  
14.3 Transport hazard class(es) : 8  
14.4 Packing group : III  
14.5 Environmental hazards : Yes  
14.6 Special precautions for user : None

**Air transport (IATA)**

- 14.1 UN number : 3267  
14.2 UN proper shipping name : Corrosive liquid, basic, organic, n.o.s.  
(monoethanolamine , Limonene)  
14.3 Transport hazard class(es) : 8  
14.4 Packing group : III  
14.5 Environmental hazards : Yes  
14.6 Special precautions for user : None

**Sea transport (IMDG/IMO)**

- 14.1 UN number : 3267  
14.2 UN proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.  
(monoethanolamine , Limonene)  
14.3 Transport hazard class(es) : 8  
14.4 Packing group : III  
14.5 Environmental hazards : Yes  
14.6 Special precautions for user : None  
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

**Section: 15. REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- according to Detergents Regulation EC 648/2004 : less than 5 %: Non-ionic surfactants  
Other constituents: Perfumes  
Allergens:  
Limonene

- Seveso III: Directive 2012/18/EU of the European : ENVIRONMENTAL HAZARDS E2  
Lower tier : 200 t

**Neomax BMR**

Parliament and of the Council  
on the control of major-  
accident hazards involving  
dangerous substances.

Upper tier : 500 t

Candidate List of Substances : Not applicable.  
of Very High Concern for  
Authorisation

**National Regulations**

**Take note of Dir 94/33/EC on the protection of young people at work.**

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)  
Regulations.  
The Control of Substances Hazardous to Health Regulations.  
Health and Safety at Work Act.

**15.2 Chemical Safety Assessment**

No Chemical Safety Assessment has been carried out on the product.

**Section: 16. OTHER INFORMATION****Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

| Classification                                              | Justification                       |
|-------------------------------------------------------------|-------------------------------------|
| Skin corrosion 1, H314                                      | Based on product data or assessment |
| Serious eye damage 1, H318                                  | Based on product data or assessment |
| Skin sensitization 1, H317                                  | Calculation method                  |
| Specific target organ toxicity - single exposure<br>3, H335 | Calculation method                  |
| Chronic aquatic toxicity 2, H411                            | Calculation method                  |

**Full text of H-Statements**

|      |                                                       |
|------|-------------------------------------------------------|
| H226 | Flammable liquid and vapour.                          |
| H302 | Harmful if swallowed.                                 |
| H304 | May be fatal if swallowed and enters airways.         |
| H312 | Harmful in contact with skin.                         |
| H314 | Causes severe skin burns and eye damage.              |
| H315 | Causes skin irritation.                               |
| H317 | May cause an allergic skin reaction.                  |
| H318 | Causes serious eye damage.                            |
| H319 | Causes serious eye irritation.                        |
| H332 | Harmful if inhaled.                                   |
| H335 | May cause respiratory irritation.                     |
| H400 | Very toxic to aquatic life.                           |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects.    |

**Full text of other abbreviations**

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -

**Neomax BMR**

Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Annex: Exposure Scenarios****Exposure Scenario: Floor stripper. Manual process**

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

**Contributing scenario controlling environmental exposure for:**

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment : Municipal sewage treatment plant

**Neomax BMR**

Plant

**Contributing scenario controlling worker exposure for:**

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Respiratory Protection : see section 8

Skin Protection : see section 8

**Contributing scenario controlling worker exposure for:**

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

**Exposure Scenario: Floor stripper. Semi-Automatic process**

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

**Contributing scenario controlling environmental exposure for:**

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

**Contributing scenario controlling worker exposure for:**

Process category : **PROC10** Roller application or brushing

**Neomax BMR**

Exposure duration : 480 min

Operational conditions and  
risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Respiratory Protection : see section 8

Skin Protection : see section 8

**Contributing scenario controlling worker exposure for:**

Process category : **PROC8a** Transfer of substance or preparation (charging/  
discharging) from/ to vessels/ large containers at non-  
dedicated facilities

Exposure duration : 60 min

Operational conditions and  
risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8