

Ecobrite Super Silex Liquid**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : Ecobrite Super Silex Liquid

Product code : 115611E

Use of the Substance/Mixture : Laundry detergent

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laundry detergent. Automatic process

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : +441618841235
+32-(0)3-575-5555 Trans-European

Poison Information Centre telephone number : For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 26.08.2025
Version : 5.0

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Skin irritation, Category 2 H315
Serious eye damage, Category 1 H318

2.2 Label elements

Ecobrite Super Silex Liquid**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.
H318 Causes serious eye damage.

Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ eye protection/ face protection.

Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
alcohols, c12-16, ethoxylated > 5EO

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	68411-30-3 270-115-0 01-2119489428-22	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 5 - < 10
alcohols, c12-16, ethoxylated > 5EO	68551-12-2	Acute toxicity Category 4; H302 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 3 - < 10
fatty acids, coco, compds. with triethanolamine	61790-64-5 263-155-5 REACH EXEMPTED	Eye irritation Category 2; H319	>= 1 - < 10
Fatty acids, coco, sodium salts	61789-31-9 263-050-4 EXEMPTED	Eye irritation Category 2; H319	>= 1 - < 10
Alcohols, C13, branched, ethoxylated	69011-36-5 POLYMER	Acute toxicity Category 4; H302 Serious eye damage Category 1; H318	>= 1 - < 3
sodium hydroxide	1310-73-2 215-185-5	Skin corrosion Category 1A; H314 Corrosive to metals Category 1; H290	>= 0.5 - < 1

Ecobrite Super Silex Liquid

	01-2119457892-27	Skin corrosion Category 1A H314 $\geq 5\%$ Skin corrosion Category 1B H314 2 - $< 5\%$ Skin irritation Category 2 H315 0.5 - $< 2\%$ Eye irritation Category 2 H319 0.5 - $< 2\%$	
Substances with a workplace exposure limit :			
Propylene glycol	57-55-6 200-338-0 01-2119456809-23	Not Classified;	$\geq 1 - < 10$
glycerin	56-81-5 200-289-5 01-2119471987-18	Not Classified;	$\geq 0.1 - < 1$

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Get medical attention if irritation develops and persists.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES**5.1 Extinguishing media**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Not flammable or combustible.
- Hazardous combustion : Depending on combustion properties, decomposition products

Ecobrite Super Silex Liquid

products

may include following materials:

Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides
metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Ecobrite Super Silex Liquid

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Protect from frost, heat and sunlight. Store at room temperature in the original container. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 40 °C

7.3 Specific end uses

Specific use(s) : Laundry detergent. Automatic process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Propylene glycol	57-55-6	TWA (Total vapour and particles)	150 ppm 474 mg/m ³	UKCOSSTD
		TWA (particles)	10 mg/m ³	UKCOSSTD
sodium hydroxide	1310-73-2	STEL	2 mg/m ³	UKCOSSTD
glycerin	56-81-5	TWA (Mist)	10 mg/m ³	UKCOSSTD

DNEL

benzenesulfonic acid, C10-13-alkyl derivs., sodium salt	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 85 mg/cm² End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 85 mg/cm² End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 6 mg/m³ End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 6 mg/m³
Propylene glycol	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 168 mg/m³

Ecobrite Super Silex Liquid

		End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m³ End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 50 mg/m³ End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m³ End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects 213 mg/kg End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 85 ppm
sodium hydroxide	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m³ End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m³

PNEC

benzenesulfonic acid, C10-13-alkyl derivs., sodium salt	:	Fresh water Value: 0.268 mg/l Marine water Value: 0.0268 mg/l Intermittent use/release Value: 0.0167 mg/l Fresh water sediment Value: 8.1 mg/kg Marine sediment Value: 8.1 mg/kg Sewage treatment plant Value: 3.43 mg/l
---	---	--

Ecobrite Super Silex Liquid

Propylene glycol	:	Fresh water Value: 260 mg/l
		Marine water Value: 26 mg/l
		Intermittent use/release Value: 183 mg/l
		Fresh water sediment Value: 572 mg/kg
		Marine sediment Value: 57.2 mg/kg
		Sewage treatment plant Value: 20000 mg/l
		Soil Value: 50 mg/kg

8.2 Exposure controls**Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.3 mm for nitrile rubber 0.2 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when

Ecobrite Super Silex Liquid

respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: clear, green
Odour	: Perfumes, fragrances
pH	: 8.0 - 8.7, 100 %
Flash point	: Not applicable.
Odour Threshold	: Not applicable and/or not determined for the mixture
Melting point/freezing point	: Not applicable and/or not determined for the mixture
Initial boiling point and boiling range	: Not applicable and/or not determined for the mixture
Evaporation rate	: Not applicable and/or not determined for the mixture
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture
Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 1.03 - 1.05
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: 173.389 mm ² /s (40 °C)
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

Ecobrite Super Silex Liquid

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

In the event of fire, see Section 5

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	: There is no data available for this product.
Acute dermal toxicity	: There is no data available for this product.
Skin corrosion/irritation	: There is no data available for this product.
Serious eye damage/eye irritation	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.
Teratogenicity	: There is no data available for this product.
STOT - single exposure	: There is no data available for this product.
STOT - repeated exposure	: There is no data available for this product.

Ecobrite Super Silex Liquid

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt LD50 rat: 1,080 mg/kg
alcohols, c12-16, ethoxylated > 5EO LD50 rat: 2,000 mg/kg
fatty acids, coco, compds. with triethanolamine LD50 rat: 6,400 mg/kg
Alcohols, C13, branched, ethoxylated LD50 rat: > 500 mg/kg
Propylene glycol LD50 rat: 22,000 mg/kg
glycerin LD50 rat: 18,300 mg/kg

Components

Acute inhalation toxicity : Propylene glycol 4 h LC50 rabbit: 158.5 mg/l
Test atmosphere: dust/mist

Components

Acute dermal toxicity : glycerin LD50 rabbit: 23,000 mg/kg

Potential Health Effects

Eyes : Causes serious eye damage.
Skin : Causes skin irritation.
Ingestion : Health injuries are not known or expected under normal use.
Inhalation : Health injuries are not known or expected under normal use.
Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion
Skin contact : Redness, Irritation
Ingestion : No symptoms known or expected.
Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : no data available

Ecobrite Super Silex Liquid

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt 96 h LC50 Lepomis macrochirus (Bluegill sunfish): 1.67 mg/l

alcohols, c12-16, ethoxylated > 5EO 96 h LC50 Brachydanio rerio (zebrafish): > 1 - 10 mg/l

Alcohols, C13, branched, ethoxylated 96 h LC50 Fish: 3 mg/l

Propylene glycol 96 h LC50 Fish: > 10,000 mg/l

glycerin 96 h LC50 Fish: 855 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt 48 h LC50 Daphnia magna (Water flea): 2.4 mg/l

alcohols, c12-16, ethoxylated > 5EO 48 h EC50 Daphnia magna Straus: > 1 - 10 mg/l

Alcohols, C13, branched, ethoxylated 48 h EC50 Daphnia magna (Water flea): 1.5 mg/l

sodium hydroxide 48 h EC50 Daphnia magna (Water flea): 40 mg/l

Propylene glycol 48 h EC50 Aquatic Invertebrate: 18,340 mg/l

Components

Toxicity to algae : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt 96 h EC50 Pseudokirchneriella subcapitata (green algae): 29 mg/l

alcohols, c12-16, ethoxylated > 5EO 72 h EC50 Scenedesmus subspicatus: > 1 - 10 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt Result: Readily biodegradable.

alcohols, c12-16, ethoxylated > 5EO Result: Readily biodegradable.

fatty acids, coco, compds. with triethanolamine Result: Readily biodegradable.

Alcohols, C13, branched, ethoxylated Result: Biodegradable

Ecobrite Super Silex Liquid

sodium hydroxide Result: Not applicable - inorganic

Propylene glycol Result: Readily biodegradable.

glycerin Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

- Product : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
- Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Section: 14. TRANSPORT INFORMATION

Ecobrite Super Silex Liquid

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number	: Not dangerous goods
14.2 UN proper shipping name	: Not dangerous goods
14.3 Transport hazard class(es)	: Not dangerous goods
14.4 Packing group	: Not dangerous goods
14.5 Environmental hazards	: Not dangerous goods
14.6 Special precautions for user	: Not dangerous goods

Air transport (IATA)

14.1 UN number	: Not dangerous goods
14.2 UN proper shipping name	: Not dangerous goods
14.3 Transport hazard class(es)	: Not dangerous goods
14.4 Packing group	: Not dangerous goods
14.5 Environmental hazards	: Not dangerous goods
14.6 Special precautions for user	: Not dangerous goods

Sea transport (IMDG/IMO)

14.1 UN number	: Not dangerous goods
14.2 UN proper shipping name	: Not dangerous goods
14.3 Transport hazard class(es)	: Not dangerous goods
14.4 Packing group	: Not dangerous goods
14.5 Environmental hazards	: Not dangerous goods
14.6 Special precautions for user	: Not dangerous goods
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	: Not dangerous goods

Section: 15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

according to Detergents Regulation EC 648/2004	: 5 % or over but less than 15 %: Anionic surfactants, Soap less than 5 %: Non-ionic surfactants Other constituents: Enzymes, Optical brighteners, Perfumes Preservation agents: 2-phenoxyethanol Allergens: Hexyl cinnamal Benzyl salicylate Amyl cinnamal Limonene Geraniol
--	---

Ecobrite Super Silex Liquid

Alpha-Isomethyl Ionone

Seveso III: Directive : Not applicable.
2012/18/EU of the European
Parliament and of the Council
on the control of major-
accident hazards involving
dangerous substances.

Candidate List of Substances : Not applicable.
of Very High Concern for
Authorisation

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)
Regulations.
The Control of Substances Hazardous to Health Regulations.
Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Skin irritation 2, H315	Calculation method
Serious eye damage 1, H318	Calculation method

Full text of H-Statements

H290 May be corrosive to metals.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -

Ecobrite Super Silex Liquid

International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios**Exposure Scenario: Laundry detergent. Automatic process**

Life Cycle Stage : Use at industrial sites

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC4** Industrial use of processing aids in processes and products, not becoming part of articles

Daily amount per site : 50 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Ecobrite Super Silex Liquid

Process category : **PROC8b** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC2** Use in closed, continuous process with occasional controlled exposure

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8