

MAXX Forte2**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : MAXX Forte2
Product code : 116323E
Use of the Substance/Mixture : Floor Stripper
Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Floor stripper. Manual process
Floor stripper. Semi-Automatic process
Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : +441618841235
+32-(0)3-575-5555 Trans-European
Poison Information Centre telephone number : Not Available

Date of Compilation/Revision : 23.02.2018
Version : 2.2

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Not a hazardous substance or mixture.

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)**

MAXX Forte2

Not a hazardous substance or mixture.

Additional Labelling:

Special labelling of certain mixtures : Safety data sheet available on request.

Contains: d-Limonene, May produce an allergic reaction.

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	ClassificationREGULATION (EC) No 1272/2008	Concentration: [%]
Sodiumcumenesulphonate	28348-53-0 248-983-7	Eye irritation Category 2; H319	>= 3 - < 5
diphosphoric acid, tetrapotassium salt	7320-34-5 230-785-7 01-2119489369-18	Eye irritation Category 2; H319	>= 1 - < 2.5
2-phenoxyethanol	122-99-6 204-589-7 01-2119488943-21	Acute toxicity Category 4; H302 Eye irritation Category 2; H319	>= 1 - < 2.5
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 01-2119475104-44	Eye irritation Category 2; H319	>= 1 - < 2.5
Fattyalcohol ethoxylates > 5EO	146340-16-1	Skin irritation Category 2; H315 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 3; H412	>= 1 - < 2.5
Substances with a workplace exposure limit :			
1-(2-methoxy-2-methylethoxy)-2-propanol	34590-94-8 252-104-2 01-2119971060-47	Not Classified;	>= 5 - < 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

MAXX Forte2

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : No specific measures identified.

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides
Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel : Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Environmental precautions : No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material

MAXX Forte2

or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
 For personal protection see section 8.
 See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling : Wash hands after handling. For personal protection see section 8.
 Hygiene measures : Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
 Storage temperature : -5 °C to 40 °C

7.3 Specific end uses

Specific use(s) : Floor stripper. Manual process
 Floor stripper. Semi-Automatic process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
1-(2-methoxy-2-methylethoxy)-2-propanol	34590-94-8	TWA	50 ppm 308 mg/m3	UKCOSSTD
Further information	Sk	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
	2	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used		
2-(2-butoxyethoxy)ethanol	112-34-5	TWA	10 ppm 67.5 mg/m3	UKCOSSTD
		STEL	15 ppm 101.2 mg/m3	UKCOSSTD
ammonium hydroxide	1336-21-6	TWA	25 ppm 18 mg/m3	UKCOSSTD
		STEL	35 ppm 25 mg/m3	UKCOSSTD

DNEL

2-(2-butoxyethoxy)ethanol	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 101.2 mg/m3
---------------------------	---	---

MAXX Forte2

	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 20 mg/kg
	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 67.5 mg/m3
	End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 67.5 mg/m3

PNEC

2-(2-butoxyethoxy)ethanol	:	Fresh water Value: 1 mg/l
		Marine water Value: 0.1 mg/l
		Intermittent use/release Value: 3.9 mg/l
		Sewage treatment plant Value: 200 mg/l
		Sediment Value: 4 mg/kg
		Soil Value: 0.4 mg/kg
		Oral Value: 56 mg/kg

8.2 Exposure controls

Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands before breaks and immediately after handling the product.

Eye/face protection (EN 166) : No special protective equipment required.

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection (EN 14605) : No special protective equipment required.

MAXX Forte2

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, 89/686/EEC), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : clear, colourless
Odour : ammoniacal
pH : 10.1 - 10.5, 100 %
Flash point : Not applicable.
Odour Threshold : Not applicable and/or not determined for the mixture
Melting point/freezing point : Not applicable and/or not determined for the mixture
Initial boiling point and boiling range : > 100 °C
Evaporation rate : Not applicable and/or not determined for the mixture
Flammability (solid, gas) : Not applicable and/or not determined for the mixture
Upper explosion limit : Not applicable and/or not determined for the mixture
Lower explosion limit : Not applicable and/or not determined for the mixture
Vapour pressure : Not applicable and/or not determined for the mixture
Relative vapour density : Not applicable and/or not determined for the mixture
Relative density : 1.035 - 1.045
Water solubility : soluble
Solubility in other solvents : Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water : Not applicable and/or not determined for the mixture
Auto-ignition temperature : Not applicable and/or not determined for the mixture
Thermal decomposition : Not applicable and/or not determined for the mixture
Viscosity, kinematic : Not applicable and/or not determined for the mixture
Explosive properties : Not applicable and/or not determined for the mixture
Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

MAXX Forte2

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Noble metals

10.6 Hazardous decomposition products

Decomposition products may include the following materials:

Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity : There is no data available for this product.
Acute dermal toxicity : There is no data available for this product.
Skin corrosion/irritation : There is no data available for this product.
Serious eye damage/eye irritation : There is no data available for this product.
Respiratory or skin sensitization : There is no data available for this product.
Carcinogenicity : There is no data available for this product.
Reproductive effects : There is no data available for this product.

MAXX Forte2

- Germ cell mutagenicity : There is no data available for this product.
- Teratogenicity : There is no data available for this product.
- STOT - single exposure : There is no data available for this product.
- STOT - repeated exposure : There is no data available for this product.
- Aspiration toxicity : There is no data available for this product.

Components

- Acute oral toxicity : Sodiumcumenesulphonate
LD50 rat: > 7,000 mg/kg
- diphosphoric acid, tetrapotassium salt
LD50 rat: > 2,000 mg/kg
- 2-phenoxyethanol
LD50 rat: 2,000 mg/kg
- 2-(2-butoxyethoxy)ethanol
LD50 rat: 3,306 mg/kg
- Fattyalcohol ethoxylates > 5EO
LD50 rat: > 2,000 mg/kg
- 1-(2-methoxy-2-methylethoxy)-2-propanol
LD50 rat: 5,135 mg/kg

Components

- Acute inhalation toxicity : Sodiumcumenesulphonate
4 h LC50 rat: > 770 mg/l
Test atmosphere: dust/mist

Components

- Acute dermal toxicity : Sodiumcumenesulphonate
LD50 rabbit: > 2,000 mg/kg
- 2-phenoxyethanol
LD50 rabbit: 2,250 mg/kg
- 2-(2-butoxyethoxy)ethanol
LD50 rabbit: 2,764 mg/kg
- 1-(2-methoxy-2-methylethoxy)-2-propanol
LD50 rabbit: 9,510 mg/kg

Potential Health Effects

- Eyes : Health injuries are not known or expected under normal use.
- Skin : Health injuries are not known or expected under normal use.
- Ingestion : Health injuries are not known or expected under normal use.
- Inhalation : Health injuries are not known or expected under normal use.

MAXX Forte2

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : No symptoms known or expected.

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : Sodiumcumenesulphonate
96 h LC50 Fish: > 450 mg/l

2-phenoxyethanol
96 h LC50 Fish: > 220 mg/l

2-(2-butoxyethoxy)ethanol
96 h LC50 Fish: 1,300 mg/l

Fattyalcohol ethoxylates > 5EO
LC50 Leuciscus idus (Golden orfe): 0.6 mg/l

1-(2-methoxy-2-methylethoxy)-2-propanol
96 h LC50 Fish: > 1,000 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : diphosphoric acid, tetrapotassium salt
48 h EC50 Daphnia: > 100 mg/l

Fattyalcohol ethoxylates > 5EO
LC50: 1.2 mg/l

Components

Toxicity to algae : Fattyalcohol ethoxylates > 5EO
96 h NOEC Desmodesmus subspicatus (green algae): 0.3 mg/l

12.2 Persistence and degradability

Product

MAXX Forte2

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : Sodiumcumenesulphonate
Result: Readily biodegradable.

diphosphoric acid, tetrapotassium salt
Result: Not applicable - inorganic

2-phenoxyethanol
Result: Readily biodegradable.

2-(2-butoxyethoxy)ethanol
Result: Readily biodegradable.

Fattyalcohol ethoxylates > 5EO
Result: Readily biodegradable.

1-(2-methoxy-2-methylethoxy)-2-propanol
Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product : Diluted product can be flushed to sanitary sewer.

Contaminated packaging : Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It

MAXX Forte2

is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- 14.1 UN number : Not dangerous goods
- 14.2 UN proper shipping name : Not dangerous goods
- 14.3 Transport hazard class(es) : Not dangerous goods
- 14.4 Packing group : Not dangerous goods
- 14.5 Environmental hazards : Not dangerous goods
- 14.6 Special precautions for user : Not dangerous goods

Air transport (IATA)

- 14.1 UN number : Not dangerous goods
- 14.2 UN proper shipping name : Not dangerous goods
- 14.3 Transport hazard class(es) : Not dangerous goods
- 14.4 Packing group : Not dangerous goods
- 14.5 Environmental hazards : Not dangerous goods
- 14.6 Special precautions for user : Not dangerous goods

Sea transport (IMDG/IMO)

- 14.1 UN number : Not dangerous goods
- 14.2 UN proper shipping name : Not dangerous goods
- 14.3 Transport hazard class(es) : Not dangerous goods
- 14.4 Packing group : Not dangerous goods
- 14.5 Environmental hazards : Not dangerous goods
- 14.6 Special precautions for user : Not dangerous goods
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not dangerous goods

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- according to Detergents Regulation EC 648/2004 : less than 5 %: Phosphates, Non-ionic surfactants
Other constituents: Perfumes

MAXX Forte2

Preservation agents:
2-phenoxyethanol
Allergens:
d-Limonene
Contains: Perfumes

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.
The Control of Substances Hazardous to Health Regulations.
Health and Safety at Work Act.

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Not a hazardous substance or mixture.	Calculation method

Full text of H-Statements

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS

MAXX Forte2

– Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Floor stripper. Manual process

Life Cycle Stage : Widespread use by professional workers
Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems
Daily amount per site : 7.5 kg
Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing
Exposure duration : 480 min
Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

MAXX Forte2

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/
discharging) from/ to vessels/ large containers at non-
dedicated facilities

Exposure duration : 60 min

Operational conditions and : Indoor
risk management measures

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : Yes: See Section 8

Respiratory Protection : No