

MAXX Satin2**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : MAXX Satin2

Product code : 117055E

Use of the Substance/Mixture : Floor care product

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Polish / impregnating agent. Manual process

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : +441618841235
+32-(0)3-575-5555 Trans-European

Poison Information Centre telephone number : For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 19.05.2023
Version : 1.2

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

MAXX Satin2**Labelling (REGULATION (EC) No 1272/2008)**

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling:

Special labelling of certain mixtures : Safety data sheet available on request.

Contains: 1,2-benzisothiazol-3(2H)-one, A mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), May produce an allergic reaction.

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 01-2120761540-60	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Skin sensitization Category 1; H317 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410 Skin sensitization Category 1 H317 ≥ 0.05 %	≥ 0.0025 - < 0.025
A mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 01-2120764691-48	Acute toxicity Category 3; H301 Acute toxicity Category 2; H330 Acute toxicity Category 2; H310 Skin corrosion Sub-category 1C; H314 Serious eye damage Category 1; H318 Skin sensitization Category 1A; H317 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410 Skin corrosion Category 1C H314 ≥ 0.6 % Skin irritation Category 2 H315 0.06 - < 0.6 % Eye irritation Category 2 H319 0.06 - < 0.6 % Skin sensitization Category 1A H317 ≥ 0.0015 % Serious eye damage Category 1 H318 ≥ 0.6 % M = 100 M(Chronic) = 100	≥ 0.0002 - < 0.0015

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures**

MAXX Satin2

- | | |
|-------------------------|---|
| In case of eye contact | : Rinse with plenty of water. |
| In case of skin contact | : Rinse with plenty of water. |
| If swallowed | : Rinse mouth. Get medical attention if symptoms occur. |
| If inhaled | : Get medical attention if symptoms occur. |

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- | | |
|-----------|------------------------------------|
| Treatment | : No specific measures identified. |
|-----------|------------------------------------|

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | : None known. |

5.2 Special hazards arising from the substance or mixture

- | | |
|--------------------------------------|---|
| Specific hazards during firefighting | : Not flammable or combustible. |
| Hazardous combustion products | : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NOx) |

5.3 Advice for firefighters

- | | |
|---|---|
| Special protective equipment for firefighters | : Use personal protective equipment. |
| Further information | : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

- | | |
|------------------------------------|--|
| Advice for non-emergency personnel | : Refer to protective measures listed in sections 7 and 8. |
| Advice for emergency responders | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. |

6.2 Environmental precautions

- | | |
|---------------------------|--|
| Environmental precautions | : No special environmental precautions required. |
|---------------------------|--|

MAXX Satin2**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE**7.1 Precautions for safe handling**

Advice on safe handling : Wash hands after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE). For personal protection see section 8.

Hygiene measures : Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 40 °C

7.3 Specific end uses

Specific use(s) : Polish / impregnating agent. Manual process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Ethylene Glycol	107-21-1	TWA (particles)	10 mg/m ³	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA (Vapour.)	20 ppm 52 mg/m ³	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL (Vapour.)	40 ppm 104 mg/m ³	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		

MAXX Satin2

DNEL

2-(2-ethoxyethoxy)ethanol	: End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 83 mg/cm² End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 61 mg/m³ End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 30 mg/m³ End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 25 mg/cm² End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 37 mg/m³ End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 50 ppm End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 18 mg/m³
Ethylene Glycol	: End Use: Workers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 106 mg/cm² End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 35 mg/m³ End Use: Consumers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 53 mg/cm² End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 7 mg/m³

MAXX Satin2

PNEC

2-(2-ethoxyethoxy)ethanol	:	Fresh water Value: 19.8 mg/l Marine water Value: 0.198 mg/l Soil Value: 0.34 mg/kg Fresh water sediment Value: 7.32 mg/kg Marine sediment Value: 0.732 mg/kg Sewage treatment plant Value: 500 mg/l Oral Value: 444 mg/kg
Ethylene Glycol	:	Fresh water Value: 10 mg/l Marine water Value: 1 mg/l Water Value: 10 mg/l Fresh water sediment Value: 20.9 mg/kg Water Value: 1995.5 mg/l Soil Value: 1.53 mg/kg

8.2 Exposure controls**Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands before breaks and immediately after handling the product.

Eye/face protection (EN 166) : No special protective equipment required.

Hand protection (EN 374) : No special protective equipment required.

MAXX Satin2

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

Appearance	: Emulsion
Colour	: white
Odour	: Perfumes, fragrances
pH	: 8.1 - 8.9, 100 %
Flash point	: Not applicable.
Odour Threshold	: Not applicable and/or not determined for the mixture
Melting point/freezing point	: Not applicable and/or not determined for the mixture
Initial boiling point and boiling range	: Not applicable and/or not determined for the mixture
Evaporation rate	: Not applicable and/or not determined for the mixture
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture
Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 1.022 - 1.03
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: 19.490 mm ² /s (40 °C)
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

MAXX Satin2

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides

nitrogen oxides (NO_x)

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : There is no data available for this product.

Acute inhalation toxicity : There is no data available for this product.

Acute dermal toxicity : There is no data available for this product.

Skin corrosion/irritation : There is no data available for this product.

Serious eye damage/eye irritation : There is no data available for this product.

Respiratory or skin sensitization : There is no data available for this product.

Carcinogenicity : There is no data available for this product.

MAXX Satin2

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : 1,2-benzisothiazol-3(2H)-one LD50 rat: 670 mg/kg

A mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) LD50 rat: 64 mg/kg

Components

Acute inhalation toxicity : A mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) 4 h LC50 rat: 0.33 mg/l
Test atmosphere: dust/mist

Components

Acute dermal toxicity : A mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) LD50 rabbit: 87.12 mg/kg

Potential Health Effects

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : No symptoms known or expected.

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Environmental Effects : This product has no known ecotoxicological effects.

MAXX Satin2

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : 1,2-benzisothiazol-3(2H)-one96 h LC50 Oncorhynchus mykiss (rainbow trout): 2.18 mg/l

A mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)96 h LC50 Oncorhynchus mykiss (rainbow trout): 0.19 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : 1,2-benzisothiazol-3(2H)-one48 h EC50 Daphnia magna (Water flea): 2.94 mg/l

A mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)48 h LC50 Daphnia magna (Water flea): 0.16 mg/l

Components

Toxicity to algae : 1,2-benzisothiazol-3(2H)-one72 h EC50 Pseudokirchneriella subcapitata (algae): 0.11 mg/l

A mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)72 h LC50 Skeletonema costatum (marine diatom): 0.037 mg/l

12.2 Persistence and degradability

Product

no data available

Components

Biodegradability : 1,2-benzisothiazol-3(2H)-oneResult: Biodegradable

A mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)Result: Biodegradable

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very

MAXX Satin2

persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

- | | |
|-----------------------------------|--|
| Product | : Diluted product can be flushed to sanitary sewer if regulations permit. |
| Contaminated packaging | : Dispose of in accordance with local, state, and federal regulations. |
| Guidance for Waste Code selection | : Organic wastes containing not dangerous substances with concentration $\geq 0.1\%$. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations. |

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- | | |
|-----------------------------------|-----------------------|
| 14.1 UN number | : Not dangerous goods |
| 14.2 UN proper shipping name | : Not dangerous goods |
| 14.3 Transport hazard class(es) | : Not dangerous goods |
| 14.4 Packing group | : Not dangerous goods |
| 14.5 Environmental hazards | : Not dangerous goods |
| 14.6 Special precautions for user | : Not dangerous goods |

Air transport (IATA)

- | | |
|---------------------------------|-----------------------|
| 14.1 UN number | : Not dangerous goods |
| 14.2 UN proper shipping name | : Not dangerous goods |
| 14.3 Transport hazard class(es) | : Not dangerous goods |
| 14.4 Packing group | : Not dangerous goods |
| 14.5 Environmental hazards | : Not dangerous goods |
| 14.6 Special precautions for | : Not dangerous goods |

MAXX Satin2

user

Sea transport (IMDG/IMO)

14.1 UN number : Not dangerous goods
 14.2 UN proper shipping name : Not dangerous goods
 14.3 Transport hazard class(es) : Not dangerous goods
 14.4 Packing group : Not dangerous goods
 14.5 Environmental hazards : Not dangerous goods
 14.6 Special precautions for user : Not dangerous goods
 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not dangerous goods

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents Regulation EC 648/2004 : Preservation agents:
 sodium pyrrithione
 1,2-benzisothiazol-3(2H)-one
 A mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable.

Candidate List of Substances of Very High Concern for Authorisation : Not applicable.

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.
 The Control of Substances Hazardous to Health Regulations.
 Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Not a hazardous substance or mixture.	Calculation method

Full text of H-Statements

MAXX Satin2

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

MAXX Satin2

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Polish / impregnating agent. Manual process

Life Cycle Stage : Widespread use by professional workers

Product category : **PC31** Polishes and wax blends

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8