



LIQUIDSENSE MULTIPURPOSE CLEANER

Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name : LIQUIDSENSE MULTIPURPOSE CLEANER

Product code : 115495E

Use of the Substance/Mixture : All Purpose Cleaner

Substance type: : Mixture

For professional users only.

Product dilution information : 0.2 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : General purpose cleaner - Manual process, without PPE

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : KAY BV
Havenlaan 4
B-3980 Tessenderlo, Belgium +32 13 67 06 90 (Belgium)
BEKAYcustomerservice@ecolab.com

Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : +441618841235
+32-(0)3-575-5555 Trans-European

Poison Information Centre telephone number : For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 22.11.2023
Version : 4.1

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

LIQUIDSENSE MULTIPURPOSE CLEANER**Product AS SOLD**

Skin irritation, Category 2

H315

Serious eye damage, Category 1

H318

Chronic aquatic toxicity, Category 3

H412

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)****Product AS SOLD**

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H315
H318
H412

Causes skin irritation.

Causes serious eye damage.

Harmful to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**

P273

Avoid release to the environment.

Response:

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt

N,N-Dimethyldodecylamine N-oxide

Product AT USE DILUTION

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling:**Product AS SOLD**

Special labelling of certain mixtures

: Contains: Limonene, May produce an allergic reaction.

2.3 Other hazards**Product AS SOLD**

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Product AS SOLD****Hazardous components**

Chemical Name	CAS-No.	Classification	Concentration
---------------	---------	----------------	---------------

LIQUIDSENSE MULTIPURPOSE CLEANER

	EC-No. REACH No.	REGULATION (EC) No 1272/2008	: [%]
Secondary Alkanesulphonates	68439-57-6 270-407-8 01-2119513401-57	Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Serious eye damage/eye irritation Category 1 > 38 - 100 % Serious eye damage/eye irritation Category 2A > 30 - 38 % Serious eye damage/eye irritation Category 2B 5 - 30 % Skin corrosion/irritation Category 2 5 - 100 %	>= 5 - < 10
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	68891-38-3 500-234-8 01-2119488639-16	Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412 Serious eye damage/eye irritation Category 1 10 - 100 % Serious eye damage/eye irritation Category 2A > 5 - < 10 %	>= 3 - < 5
Amines, C12-14 alkyldimethyl, N-oxides	308062-28-4 01-2119490061-47	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 2; H411 M = 1	>= 3 - < 5
Sodium Xylenesulfonate	1300-72-7 215-090-9 01-2119513350-56	Eye irritation Category 2; H319	>= 1 - < 2.5
Limonene	5989-27-5 227-813-5 01-2119529223-47	Nota C Flammable liquids Category 3; H226 Skin irritation Category 2; H315 Skin sensitization Category 1; H317 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410 Aspiration hazard Category 1; H304 M = 1 M(Chronic) = 1	>= 0.1 - < 0.25

Product AT USE DILUTION

Remarks : No hazardous ingredients

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures****Product AS SOLD**

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Get medical attention if irritation

LIQUIDSENSE MULTIPURPOSE CLEANER

develops and persists.

- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Product AT USE DILUTION

- In case of eye contact : Rinse with plenty of water.
- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Not flammable or combustible.
- Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides
metal oxides

5.3 Advice for firefighters

- Special protective equipment for firefighters : Use personal protective equipment.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

LIQUIDSENSE MULTIPURPOSE CLEANER

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency personnel : Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

Environmental precautions : No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.

For personal protection see section 8.

See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

LIQUIDSENSE MULTIPURPOSE CLEANER**Product AS SOLD**

- Advice on safe handling : Avoid contact with skin and eyes. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

- Advice on safe handling : Wash hands after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE). For personal protection see section 8.
- Hygiene measures : Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities**Product AS SOLD**

- Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
- Storage temperature : 5 °C to 50 °C

Product AT USE DILUTION

- Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses**Product AS SOLD****Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters****Product AS SOLD**

Contains no substances with occupational exposure limit values.

DNEL

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 175 mg/m3
	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 2750 mg/m3
	:	End Use: Workers

LIQUIDSENSE MULTIPURPOSE CLEANER

	Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.132 mg/m3 End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 52 mg/m3 End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 1650 mg/m3 End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.079 mg/m3 End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 15 mg/m3
--	---

PNEC

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	: Fresh water Value: 0.24 mg/l Marine water Value: 0.024 mg/l Sewage treatment plant Value: 10000 mg/l Fresh water sediment Value: 0.917 mg/kg Marine sediment Value: 0.092 mg/kg Soil Value: 7.5 mg/kg
--	---

8.2 Exposure controls**Product AS SOLD****Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use.

LIQUIDSENSE MULTIPURPOSE CLEANER

Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

- Eye/face protection (EN 166) : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.
In case of contact through splashing:
Safety goggles
Face-shield
- Hand protection (EN 374) : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.
In case of contact through splashing:
Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.3 mm for nitrile rubber 0.2 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Skin and body protection (EN 14605) : No special protective equipment required.
- Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Product AT USE DILUTION

Appropriate engineering controls

- Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

- Hygiene measures : Wash hands before breaks and immediately after handling the product.
- Eye/face protection (EN 166) : No special protective equipment required.
- Hand protection (EN 374) : No special protective equipment required.
- Skin and body protection (EN 14605) : No special protective equipment required.
- Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods

LIQUIDSENSE MULTIPURPOSE CLEANER

or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Colour	: clear, blue	colourless
Odour	: citrus	citrus
pH	: 6.0 - 9.0, 100 %	6.0 - 9.0
Flash point	: Not applicable.	
Odour Threshold	: Not applicable and/or not determined for the mixture	
Melting point/freezing point	: Not applicable and/or not determined for the mixture	
Initial boiling point and boiling range	: > 100 °C	
Evaporation rate	: Not applicable and/or not determined for the mixture	
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture	
Upper explosion limit	: Not applicable and/or not determined for the mixture	
Lower explosion limit	: Not applicable and/or not determined for the mixture	
Vapour pressure	: Not applicable and/or not determined for the mixture	
Relative vapour density	: Not applicable and/or not determined for the mixture	
Relative density	: 1.025 - 1.045	
Water solubility	: soluble	
Solubility in other solvents	: Not applicable and/or not determined for the mixture	
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture	
Auto-ignition temperature	: Not applicable and/or not determined for the mixture	
Thermal decomposition	: Not applicable and/or not determined for the mixture	
Viscosity, kinematic	: Not applicable and/or not determined for the mixture	
Explosive properties	: Not applicable and/or not determined for the mixture	
Oxidizing properties	: The substance or mixture is not classified as oxidizing.	

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY**Product AS SOLD****10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

LIQUIDSENSE MULTIPURPOSE CLEANER

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
metal oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product AS SOLD

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	: There is no data available for this product.
Acute dermal toxicity	: There is no data available for this product.
Skin corrosion/irritation	: There is no data available for this product.
Serious eye damage/eye irritation	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.
Teratogenicity	: There is no data available for this product.

LIQUIDSENSE MULTIPURPOSE CLEANER

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : Secondary Alkanesulphonates LD50 rat: 2,079 mg/kg
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt LD50 rat: 3,350 mg/kg
Amines, C12-14 alkyl dimethyl, N-oxides LD50 rat: 1,064 mg/kg
Sodium Xylenesulfonate LD50 rat: > 7,000 mg/kg
Limonene LD50 rat: 4,400 mg/kg

Components

Acute inhalation toxicity : Secondary Alkanesulphonates 4 h LC50 rat: > 52 mg/l
Test atmosphere: dust/mist

Components

Acute dermal toxicity : Secondary Alkanesulphonates LD50 rabbit: 6,300 mg/kg
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt LD50 rat: 8,000 mg/kg
Limonene LD50 rabbit: > 5,000 mg/kg

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye damage.
Skin : Causes skin irritation.
Ingestion : Health injuries are not known or expected under normal use.
Inhalation : Health injuries are not known or expected under normal use.
Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Health injuries are not known or expected under normal use.
Skin : Health injuries are not known or expected under normal use.
Ingestion : Health injuries are not known or expected under normal use.
Inhalation : Health injuries are not known or expected under normal use.
Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

LIQUIDSENSE MULTIPURPOSE CLEANER

Product AS SOLD

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Irritation
Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.

Product AT USE DILUTION

Eye contact	: No symptoms known or expected.
Skin contact	: No symptoms known or expected.
Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Product AS SOLD

Environmental Effects	: Harmful to aquatic life with long lasting effects.
-----------------------	--

Product AT USE DILUTION

Environmental Effects	: This product has no known ecotoxicological effects.
-----------------------	---

Product AS SOLD

Product

Toxicity to fish	: no data available
Toxicity to daphnia and other aquatic invertebrates	: no data available
Toxicity to algae	: no data available

Components

Toxicity to fish	: Secondary Alkanesulphonates96 h LC50 Danio rerio (zebra fish): 4.2 mg/l Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt96 h LC50 Danio rerio (zebra fish): 7.1 mg/l Amines, C12-14 alkyl dimethyl, N-oxides96 h LC50: 2.67 mg/l
------------------	--

Components

Toxicity to daphnia and other aquatic invertebrates	: Secondary Alkanesulphonates48 h EC50 Ceriodaphnia dubia (water flea): 4.53 mg/l Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt48 h EC50 Daphnia magna (Water flea): 7.4 mg/l Amines, C12-14 alkyl dimethyl, N-oxides48 h EC50 Daphnia magna (Water flea): 3.1 mg/l Limonene48 h EC50 Daphnia magna (Water flea): 0.307 mg/l
---	--

LIQUIDSENSE MULTIPURPOSE CLEANER

Components

Toxicity to algae : Secondary Alkanesulphonates 72 h EC50 *Skeletonema costatum* (marine diatom): 5.2 mg/l

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt 72 h EC50 *Desmodesmus subspicatus* (green algae): 27.7 mg/l

Amines, C12-14 alkyldimethyl, N-oxides 72 h LC50: 0.143 mg/l
72 h NOEC: 0.067 mg/l

Sodium Xylenesulfonate 96 h EC50: 230 mg/l

Limonene 72 h EC50 *Pseudokirchneriella subcapitata* (algae): 0.32 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : Secondary Alkanesulphonates Result: Readily biodegradable.

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt Result: Readily biodegradable.

Amines, C12-14 alkyldimethyl, N-oxides Result: Readily biodegradable.

Sodium Xylenesulfonate Result: Biodegradable

Limonene Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

LIQUIDSENSE MULTIPURPOSE CLEANER

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods**Product AS SOLD**

- | | | |
|-----------------------------------|---|---|
| Product | : | Do not contaminate storm water drains, natural waterways or soil with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility. |
| Contaminated packaging | : | Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations. |
| Guidance for Waste Code selection | : | Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations. |

Product AT USE DILUTION

- | | | |
|------------------------|---|---|
| Product | : | Diluted product can be flushed to sanitary sewer if regulations permit. |
| Contaminated packaging | : | Dispose of in accordance with local, state, and federal regulations. |

Section: 14. TRANSPORT INFORMATION**Product AS SOLD**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- | | | |
|-----------------------------------|---|---------------------|
| 14.1 UN number | : | Not dangerous goods |
| 14.2 UN proper shipping name | : | Not dangerous goods |
| 14.3 Transport hazard class(es) | : | Not dangerous goods |
| 14.4 Packing group | : | Not dangerous goods |
| 14.5 Environmental hazards | : | Not dangerous goods |
| 14.6 Special precautions for user | : | Not dangerous goods |

Air transport (IATA)

- | | | |
|------------------------------|---|---------------------|
| 14.1 UN number | : | Not dangerous goods |
| 14.2 UN proper shipping name | : | Not dangerous goods |

LIQUIDSENSE MULTIPURPOSE CLEANER

14.3 Transport hazard class(es) : Not dangerous goods
 14.4 Packing group : Not dangerous goods
 14.5 Environmental hazards : Not dangerous goods
 14.6 Special precautions for user : Not dangerous goods

Sea transport (IMDG/IMO)

14.1 UN number : Not dangerous goods
 14.2 UN proper shipping name : Not dangerous goods
 14.3 Transport hazard class(es) : Not dangerous goods
 14.4 Packing group : Not dangerous goods
 14.5 Environmental hazards : Not dangerous goods
 14.6 Special precautions for user : Not dangerous goods
 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not dangerous goods

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents Regulation EC 648/2004 : 5 % or over but less than 15 %: Anionic surfactants
 less than 5 %: Non-ionic surfactants
 Other constituents: Perfumes
 Preservation agents:
 2-phenoxyethanol
 3-Iodo-2-propynyl butylcarbamate
 Allergens:
 Limonene
 Citral

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable.

Candidate List of Substances of Very High Concern for Authorisation : Not applicable.

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.
 The Control of Substances Hazardous to Health Regulations.
 Health and Safety at Work Act.

15.2 Chemical Safety Assessment

LIQUIDSENSE MULTIPURPOSE CLEANER

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Skin irritation 2, H315	Calculation method
Serious eye damage 1, H318	Calculation method
Chronic aquatic toxicity 3, H412	Calculation method

Full text of H-Statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

LIQUIDSENSE MULTIPURPOSE CLEANER

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: General purpose cleaner - Manual process, without PPE

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-

LIQUIDSENSE MULTIPURPOSE CLEANER

dedicated facilities

Exposure duration : 60 min

Operational conditions and
risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8