

**ASEPTOPOL EL 75****Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : ASEPTOPOL EL 75

Product code : 114813E

Use of the
Substance/Mixture : Cleaner and disinfectant

Substance type: : Mixture

For professional users only.

Product dilution information : 0.5 % - 2.0 %

1.2 Relevant identified uses of the substance or mixture and uses advised againstIdentified uses : General purpose cleaner. Manual process
Dishwash product. Manual process
Biocide. Spray and rinse manual processRecommended restrictions
on use : Reserved for industrial and professional use.**1.3 Details of the supplier of the safety data sheet**Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com**1.4 Emergency telephone number**Emergency telephone : +441618841235
number : +32-(0)3-575-5555 Trans-EuropeanDate of Compilation/Revision : 28.07.2020
Version : 3.3**Section: 2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)****Product AS SOLD**

Serious eye damage, Category 1 H318

Chronic aquatic toxicity, Category 1 H410

The classification of this product is based on toxicological assessment.

Product AT USE DILUTION

ASEPTOPOL EL 75

Not a hazardous substance or mixture.

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)****Product AS SOLD**

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H318
H410

Causes serious eye damage.

Very toxic to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**

P273

Avoid release to the environment.

P280e

Wear eye protection/face protection.

Response:

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Alcohols, C9-11, ethoxylated

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine

Didecyl Dimethyl Ammonium Chloride

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.3 Other hazards**Product AS SOLD**

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Product AS SOLD****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
Alcohols, C9-11, ethoxylated	68439-46-3 01-2119979533-26	Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 10 - < 20
Cocamidopropyl Betaine	61789-40-0 263-058-8 01-2120770501-61	Serious eye damage Category 1; H318	>= 2.5 - < 3
N-(3-aminopropyl)-N-dodecylpropane-1,3-	2372-82-9 219-145-8	Acute toxicity Category 3; H301 Skin corrosion Category 1A; H314	>= 1 - < 2.5

ASEPTOPOL EL 75

diamine	01-2119980592-29	Serious eye damage Category 1; H318 Specific target organ toxicity - repeated exposure Category 2; H373 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410	
Didecyl Dimethyl Ammonium Chloride	7173-51-5 230-525-2 01-2119945987-15	Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Chronic aquatic toxicity Category 2; H411 Acute aquatic toxicity Category 1; H400	>= 1 - < 2.5
Substances with a workplace exposure limit :			
ethanol	64-17-5 200-578-6 01-2119457610-43	Flammable liquids Category 2; H225	>= 1 - < 2.5
Isopropyl Alcohol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 0.5 - < 1

Product AT USE DILUTION
Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine	2372-82-9 219-145-8 01-2119980592-29	Acute toxicity Category 3; H301 Skin corrosion Category 1A; H314 Serious eye damage Category 1; H318 Specific target organ toxicity - repeated exposure Category 2; H373 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410	< 0.1
Didecyl Dimethyl Ammonium Chloride	7173-51-5 230-525-2 01-2119945987-15	Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Chronic aquatic toxicity Category 2; H411 Acute aquatic toxicity Category 1; H400	< 0.1

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures****Product AS SOLD**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Product AT USE DILUTION

- In case of eye contact : Rinse with plenty of water.

ASEPTOPOL EL 75

In case of skin contact	: Rinse with plenty of water.
If swallowed	: Rinse mouth. Get medical attention if symptoms occur.
If inhaled	: Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	: Fire Hazard Keep away from heat and sources of ignition. Flash back possible over considerable distance. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Hazardous combustion products	: Depending on combustion properties, decomposition products may include following materials: Carbon oxides nitrogen oxides (NOx) Sulphur oxides Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for firefighters	: Use personal protective equipment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD

Advice for non-emergency personnel	: Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation,
------------------------------------	--

ASEPTOPOL EL 75

ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency personnel : Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

Environmental precautions : No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.

For personal protection see section 8.

See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD

Advice on safe handling : Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which

ASEPTOPOL EL 75

might cause ignition of organic vapours). Wash hands thoroughly after handling. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Advice on safe handling : Wash hands after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE). For personal protection see section 8.

Hygiene measures : Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities**Product AS SOLD**

Requirements for storage areas and containers : Keep away from heat and sources of ignition. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 40 °C

Product AT USE DILUTION

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses**Product AS SOLD****Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters****Product AS SOLD****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m ³	UKCOSSTD
Further information	16	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
Isopropyl Alcohol	67-63-0	TWA	400 ppm 999 mg/m ³	UKCOSSTD
		STEL	500 ppm 1,250 mg/m ³	UKCOSSTD

DNEL

Isopropyl Alcohol	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects
-------------------	---	---

ASEPTOPOL EL 75

	Value: 888 mg/cm ² End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 500 mg/m ³ End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 319 mg/cm ² End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m ³ End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 26 ppm
--	---

PNEC

Isopropyl Alcohol	: Fresh water Value: 140.9 mg/l Marine water Value: 140.9 mg/l Intermittent use/release Value: 140.9 mg/l Fresh water Value: 552 mg/kg Marine sediment Value: 552 mg/kg Soil Value: 28 mg/kg Sewage treatment plant Value: 2251 mg/l Oral Value: 160 mg/kg
-------------------	---

8.2 Exposure controls**Product AS SOLD****Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

ASEPTOPOL EL 75

Individual protection measures

- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.
- Eye/face protection (EN 166) : Safety goggles
Face-shield
- Hand protection (EN 374) : No special protective equipment required.
- Skin and body protection (EN 14605) : No special protective equipment required.
- Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Product AT USE DILUTION

Appropriate engineering controls

- Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

- Hygiene measures : Wash hands before breaks and immediately after handling the product.
- Eye/face protection (EN 166) : No special protective equipment required.
- Hand protection (EN 374) : No special protective equipment required.
- Skin and body protection (EN 14605) : No special protective equipment required.
- Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

- General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

ASEPTOPOL EL 75**9.1 Information on basic physical and chemical properties**

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Colour	: clear, light green	colourless
Odour	: odourless	odourless
pH	: 10.5 - 11.5, 100 %	8.8 - 9.4
Flash point	: 60 °C, Does not sustain combustion.	
Odour Threshold	: Not applicable and/or not determined for the mixture	
Melting point/freezing point	: Not applicable and/or not determined for the mixture	
Initial boiling point and boiling range	: Not applicable and/or not determined for the mixture	
Evaporation rate	: Not applicable and/or not determined for the mixture	
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture	
Upper explosion limit	: Not applicable and/or not determined for the mixture	
Lower explosion limit	: Not applicable and/or not determined for the mixture	
Vapour pressure	: Not applicable and/or not determined for the mixture	
Relative vapour density	: Not applicable and/or not determined for the mixture	
Relative density	: 0.99 - 1.03	
Water solubility	: soluble	
Solubility in other solvents	: Not applicable and/or not determined for the mixture	
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture	
Auto-ignition temperature	: Not applicable and/or not determined for the mixture	
Thermal decomposition	: Not applicable and/or not determined for the mixture	
Viscosity, kinematic	: 19.838 mm ² /s (40 °C)	
Explosive properties	: Not applicable and/or not determined for the mixture	
Oxidizing properties	: The substance or mixture is not classified as oxidizing.	

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY**Product AS SOLD****10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

ASEPTOPOL EL 75

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product AS SOLD

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	: There is no data available for this product.
Acute dermal toxicity	: There is no data available for this product.
Skin corrosion/irritation	: No skin irritation Method: OECD Test Guideline 404 Test substance: Product
Serious eye damage/eye irritation	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.
Teratogenicity	: There is no data available for this product.
STOT - single exposure	: There is no data available for this product.
STOT - repeated exposure	: There is no data available for this product.
Aspiration toxicity	: There is no data available for this product.

Components

ASEPTOPOL EL 75

Acute oral toxicity : Alcohols, C9-11, ethoxylated
LD50 rat: 4,044 mg/kg

Cocamidopropyl Betaine
LD50 rat: 2,600 mg/kg

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine
LD50 rat: 261 mg/kg

Didecyl Dimethyl Ammonium Chloride
LD50 rat: 329 mg/kg

ethanol
LD50 rat: 10,470 mg/kg

Isopropyl Alcohol
LD50 rat: 5,840 mg/kg

Components

Acute inhalation toxicity : ethanol
4 h LC50 rat: 117 mg/l
Test atmosphere: vapour

Isopropyl Alcohol
4 h LC50 rat: > 30 mg/l
Test atmosphere: vapour

Components

Acute dermal toxicity : Alcohols, C9-11, ethoxylated
LD50 rabbit: 2,108 mg/kg
Test substance: Information given is based on data obtained from similar substances.

Didecyl Dimethyl Ammonium Chloride
LD50 rabbit: 2,930 mg/kg

ethanol
LD50 rabbit: > 15,800 mg/kg

Isopropyl Alcohol
LD50 rabbit: 12,870 mg/kg

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye damage.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Health injuries are not known or expected under normal use.

ASEPTOPOL EL 75

Skin	: Health injuries are not known or expected under normal use.
Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: Health injuries are not known or expected under normal use.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact	: Redness, Pain, Corrosion
Skin contact	: No symptoms known or expected.
Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.

Product AT USE DILUTION

Eye contact	: No symptoms known or expected.
Skin contact	: No symptoms known or expected.
Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

Product AS SOLD

12.1 Ecotoxicity

Environmental Effects	: Very toxic to aquatic life with long lasting effects.
-----------------------	---

Product

Toxicity to fish	: Very toxic to aquatic life.: Test substance: Similar Product
Toxicity to daphnia and other aquatic invertebrates	: no data available
Toxicity to algae	: no data available
Toxicity to fish (Chronic toxicity)	: Very toxic to aquatic life with long lasting effects.: Test substance: Similar Product

Components

Toxicity to fish	: Alcohols, C9-11, ethoxylated 96 h LC50 Oncorhynchus mykiss (rainbow trout): 5 mg/l Cocamidopropyl Betaine 96 h LC50 Fish: 2 mg/l Didecyl Dimethyl Ammonium Chloride 96 h LC50 Fish: 1 mg/l ethanol
------------------	--

ASEPTOPOL EL 75

96 h LC50 Pimephales promelas (fathead minnow): > 100 mg/l

Isopropyl Alcohol

96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : Alcohols, C9-11, ethoxylated
48 h EC50 Daphnia magna (Water flea): 2.5 mg/l

Isopropyl Alcohol

LC50 Daphnia magna (Water flea): > 10,000 mg/l

Components

Toxicity to algae : Alcohols, C9-11, ethoxylated
96 h EC50 Pseudokirchneriella subcapitata (algae): 1.4 mg/l

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine

72 h EC50: 0.014 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : Alcohols, C9-11, ethoxylated
Result: Readily biodegradable.

Cocamidopropyl Betaine

Result: Readily biodegradable.

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine

Result: Readily biodegradable.

Didecyl Dimethyl Ammonium Chloride

Result: Eliminated from aquatic environment

ethanol

Result: Readily biodegradable.

Isopropyl Alcohol

Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

ASEPTOPOL EL 75

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD

Product : The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Product AT USE DILUTION

Product : Diluted product can be flushed to sanitary sewer if regulations permit.

Contaminated packaging : Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Alkylamine(s), Alkyl ammonium chloride)

14.3 Transport hazard : 9

ASEPTOPOL EL 75

class(es)
14.4 Packing group : III
14.5 Environmental hazards : Yes

14.6 Special precautions for user : None

Air transport (IATA)

14.1 UN number : 3082
14.2 UN proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Alkylamine(s), Alkyl ammonium chloride)
14.3 Transport hazard : 9
class(es)
14.4 Packing group : III
14.5 Environmental hazards : Yes

14.6 Special precautions for user : None

Sea transport (IMDG/IMO)

14.1 UN number : 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Alkylamine(s), Alkyl ammonium chloride)
14.3 Transport hazard : 9
class(es)
14.4 Packing group : III
14.5 Environmental hazards : Yes

14.6 Special precautions for user : None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents Regulation EC 648/2004 : 5 % or over but less than 15 %: Non-ionic surfactants
less than 5 %: Amphoteric surfactants
Contains: Disinfectants

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.
The Control of Substances Hazardous to Health Regulations.
Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

ASEPTOPOL EL 75**Section: 16. OTHER INFORMATION****Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Serious eye damage 1, H318	Calculation method
Chronic aquatic toxicity 1, H410	Calculation method

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

ASEPTOPOL EL 75

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Biocide. Spray and rinse manual process

Exposure Scenario: Dishwash product. Manual process

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

ASEPTOPOL EL 75**Contributing scenario controlling worker exposure for:**

Process category	:	PROC8a	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
Exposure duration	:	60 min	
Operational conditions and risk management measures	:	Indoor	
			Local Exhaust Ventilation is not required
General ventilation		Ventilation rate per hour	1
Skin Protection	:	see section 8	
Respiratory Protection	:	see section 8	

Exposure Scenario: General purpose cleaner. Manual process

Life Cycle Stage	:	Widespread use by professional workers
Product category	:	PC35 Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category	:	ERC8a Wide dispersive indoor use of processing aids in open systems
Daily amount per site	:	7.5 kg
Type of Sewage Treatment Plant	:	Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category	:	PROC10	Roller application or brushing
Exposure duration	:	480 min	
Operational conditions and risk management measures	:	Indoor	
			Local Exhaust Ventilation is not required
General ventilation		Ventilation rate per hour	1
Skin Protection	:	see section 8	
Respiratory Protection	:	see section 8	

Contributing scenario controlling worker exposure for:

Process category	:	PROC8a	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
------------------	---	---------------	---

ASEPTOPOL EL 75

Exposure duration : 60 min

Operational conditions and
risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8