

**LIQUIDSENSE QUARRY TILE FLOOR CLEANER****Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : LIQUIDSENSE QUARRY TILE FLOOR CLEANER

Product code : 115445E

Use of the
Substance/Mixture : Floor care product

Substance type: : Mixture

For professional users only.

Product dilution information : 0.18 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Floor cleaner - Manual process, without PPE

Recommended restrictions
on use : Reserved for industrial and professional use.**1.3 Details of the supplier of the safety data sheet**Company : KAY BV
Havenlaan 4
B-3980 Tessenderlo, Belgium +32 13 67 06 90 (Belgium)
BEKAYcustomerservice@ecolab.comEcolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com**1.4 Emergency telephone number**Emergency telephone
number : +441618841235
+32-(0)3-575-5555 Trans-EuropeanDate of Compilation/Revision : 23.02.2021
Version : 3.0**Section: 2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)****Product AS SOLD**

Skin irritation, Category 2

H315

Serious eye damage, Category 1

H318

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

Chronic aquatic toxicity, Category 3

H412

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)****Product AS SOLD**

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H315

Causes skin irritation.

H318

Causes serious eye damage.

H412

Harmful to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**

P273

Avoid release to the environment.

Response:

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.3 Other hazards**Product AS SOLD**

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Product AS SOLD****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	68411-30-3 270-115-0 01-2119489428-22	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 20 - < 25
Sodium p-	15763-76-5	Eye irritation Category 2; H319	>= 3 - < 5

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

cumenesulphonate	239-854-6 01-2119489411-37		
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	68891-38-3 500-234-8 01-2119488639-16	Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412 Serious eye damage/eye irritation Category 1 10 - 100 % Serious eye damage/eye irritation Category 2A > 5 - < 10 %	>= 2.5 - < 3
citric acid	77-92-9 201-069-1 01-2119457026-42	Corrosive to metals Category 1; H290 Eye irritation Category 2; H319 Corrosive to metals Category 1 5 - 100 %	>= 1 - < 2.5
Substances with a workplace exposure limit :			
Propylene glycol	57-55-6 200-338-0 01-2119456809-23	Not Classified;	>= 0.5 - < 1

Product AT USE DILUTION

Remarks : No hazardous ingredients

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures****Product AS SOLD**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Get medical attention if irritation develops and persists.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Product AT USE DILUTION

- In case of eye contact : Rinse with plenty of water.
- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides
metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency personnel : Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

Environmental precautions : No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.

For personal protection see section 8.

See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD

Advice on safe handling : Avoid contact with skin and eyes. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Advice on safe handling : Wash hands after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE). For personal protection see section 8.

Hygiene measures : Wash hands before breaks and immediately after handling the

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

product.

7.2 Conditions for safe storage, including any incompatibilities**Product AS SOLD**

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 50 °C

Product AT USE DILUTION

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses**Product AS SOLD**

Specific use(s) : Floor cleaner - Manual process, without PPE

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****Product AS SOLD****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Propylene glycol	57-55-6	TWA (particles)	10 mg/m ³	UKCOSSTD
		TWA (Total vapour and particles)	150 ppm 474 mg/m ³	UKCOSSTD

DNEL

benzenesulfonic acid, C10-13-alkyl derivs., sodium salt	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 85 mg/cm ²
	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 85 mg/cm ²
	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 6 mg/m ³
	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 6 mg/m ³
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects End Use: Workers

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

		Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 175 mg/m3
Propylene glycol	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 168 mg/m3 End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m3 End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 50 mg/m3 End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m3 End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 213 mg/cm2 End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 85 ppm

PNEC

benzenesulfonic acid, C10-13-alkyl derivs., sodium salt	:	Fresh water Value: 0.268 mg/l Marine water Value: 0.0268 mg/l Intermittent use/release Value: 0.0167 mg/l Fresh water sediment Value: 8.1 mg/kg Marine sediment Value: 8.1 mg/kg Sewage treatment plant Value: 3.43 mg/l
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	:	Fresh water Value: 0.24 mg/l

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

		Marine water Value: 0.024 mg/l Intermittent use/release Value: 0.071 mg/l Sewage treatment plant Value: 10000 mg/l Fresh water sediment Value: 5.45 mg/kg Marine sediment Value: 0.545 mg/kg Soil Value: 0.946 mg/kg
Propylene glycol	:	Fresh water Value: 260 mg/l Marine water Value: 26 mg/l Intermittent use/release Value: 183 mg/l Fresh water sediment Value: 572 mg/kg Marine sediment Value: 57.2 mg/kg Sewage treatment plant Value: 20000 mg/l Soil Value: 50 mg/kg

8.2 Exposure controls

Product AS SOLD

Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

- Eye/face protection (EN 166) : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.
- In case of contact through splashing:
Safety goggles
Face-shield
- Hand protection (EN 374) : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.
- In case of contact through splashing:
Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.3 mm for nitrile rubber 0.2 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Skin and body protection (EN 14605) : No special protective equipment required.
- Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Product AT USE DILUTION

Appropriate engineering controls

- Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

- Hygiene measures : Wash hands before breaks and immediately after handling the product.
- Eye/face protection (EN 166) : No special protective equipment required.
- Hand protection (EN 374) : No special protective equipment required.
- Skin and body protection (EN 14605) : No special protective equipment required.
- Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

LIQUIDSENSE QUARRY TILE FLOOR CLEANER**Environmental exposure controls**

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Colour	: clear, dark green	light green
Odour	: Perfumes, fragrances	Perfumes, fragrances
pH	: 2.6 - 3.6, 100 %	4.2
Flash point	: Not applicable.	
Odour Threshold	: Not applicable and/or not determined for the mixture	
Melting point/freezing point	: Not applicable and/or not determined for the mixture	
Initial boiling point and boiling range	: > 100 °C	
Evaporation rate	: Not applicable and/or not determined for the mixture	
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture	
Upper explosion limit	: Not applicable and/or not determined for the mixture	
Lower explosion limit	: Not applicable and/or not determined for the mixture	
Vapour pressure	: Not applicable and/or not determined for the mixture	
Relative vapour density	: Not applicable and/or not determined for the mixture	
Relative density	: 1.095 - 1.105	
Water solubility	: soluble	
Solubility in other solvents	: Not applicable and/or not determined for the mixture	
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture	
Auto-ignition temperature	: Not applicable and/or not determined for the mixture	
Thermal decomposition	: Not applicable and/or not determined for the mixture	
Viscosity, kinematic	: Not applicable and/or not determined for the mixture	
Explosive properties	: Not applicable and/or not determined for the mixture	
Oxidizing properties	: The substance or mixture is not classified as oxidizing.	

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY**Product AS SOLD****10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Chlorine-based bleaching agents
Bases
Oxidizing agents

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
metal oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product AS SOLD

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	: There is no data available for this product.
Acute dermal toxicity	: There is no data available for this product.
Skin corrosion/irritation	: There is no data available for this product.
Serious eye damage/eye irritation	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt LD50 rat: 1,080 mg/kg

Sodium p-cumenesulphonate LD50 rat: > 7,000 mg/kg

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt LD50 rat: 3,350 mg/kg

citric acid LD50 rat: 11,700 mg/kg

Propylene glycol LD50 rat: 22,000 mg/kg

Components

Acute inhalation toxicity : Propylene glycol 4 h LC50 rat: > 158.5 mg/l
Test atmosphere: dust/mist

Components

Acute dermal toxicity : Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt LD50 rabbit: 8,000 mg/kg

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye damage.

Skin : Causes skin irritation.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Irritation
Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.

Product AT USE DILUTION

Eye contact	: No symptoms known or expected.
Skin contact	: No symptoms known or expected.
Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION**Product AS SOLD****12.1 Toxicity**

Environmental Effects	: Harmful to aquatic life with long lasting effects.
-----------------------	--

Product

Toxicity to fish	: no data available
Toxicity to daphnia and other aquatic invertebrates	: no data available
Toxicity to algae	: no data available

Components

Toxicity to fish	: benzenesulfonic acid, C10-13- alkyl derivs., sodium salt96 h LC50 Lepomis macrochirus (Bluegill sunfish): 1.67 mg/l
	Sodium p-cumenesulphonate96 h LC50 Oncorhynchus mykiss (rainbow trout): > 1,000 mg/l
	Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt96 h LC50 Fish: 7.1 mg/l
	citric acid96 h LC50 Fish: > 100 mg/l
	Propylene glycol96 h LC50: > 10,000 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates	: benzenesulfonic acid, C10-13- alkyl derivs., sodium salt48 h LC50 Daphnia magna (Water flea): 2.4 mg/l
	Propylene glycol48 h EC50: 18,340 mg/l

Components

Toxicity to algae	: benzenesulfonic acid, C10-13- alkyl derivs., sodium salt96 h EC50 Pseudokirchneriella subcapitata (green algae): 29 mg/l
	Sodium p-cumenesulphonate96 h EC50 Pseudokirchneriella subcapitata (algae): > 230 mg/l

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

Propylene glycol_{96 h} EC₅₀: 19,000 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : benzenesulfonic acid, C10-13- alkyl derivs., sodium saltResult: Readily biodegradable.

Sodium p-cumenesulphonateResult: Readily biodegradable.

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium saltResult: Readily biodegradable.

citric acidResult: Readily biodegradable.

Propylene glycolResult: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste.Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD

Product : The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

- | | | |
|-----------------------------------|---|---|
| Contaminated packaging | : | Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations. |
| Guidance for Waste Code selection | : | Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations. |

Product AT USE DILUTION

- | | | |
|------------------------|---|---|
| Product | : | Diluted product can be flushed to sanitary sewer if regulations permit. |
| Contaminated packaging | : | Dispose of in accordance with local, state, and federal regulations. |

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- | | | |
|-----------------------------------|---|---------------------|
| 14.1 UN number | : | Not dangerous goods |
| 14.2 UN proper shipping name | : | Not dangerous goods |
| 14.3 Transport hazard class(es) | : | Not dangerous goods |
| 14.4 Packing group | : | Not dangerous goods |
| 14.5 Environmental hazards | : | Not dangerous goods |
| 14.6 Special precautions for user | : | Not dangerous goods |

Air transport (IATA)

- | | | |
|-----------------------------------|---|---------------------|
| 14.1 UN number | : | Not dangerous goods |
| 14.2 UN proper shipping name | : | Not dangerous goods |
| 14.3 Transport hazard class(es) | : | Not dangerous goods |
| 14.4 Packing group | : | Not dangerous goods |
| 14.5 Environmental hazards | : | Not dangerous goods |
| 14.6 Special precautions for user | : | Not dangerous goods |

Sea transport (IMDG/IMO)

- | | | |
|-------------------------|---|---------------------|
| 14.1 UN number | : | Not dangerous goods |
| 14.2 UN proper shipping | : | Not dangerous goods |

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

name
14.3 Transport hazard : Not dangerous goods
class(es)
14.4 Packing group : Not dangerous goods
14.5 Environmental hazards : Not dangerous goods
14.6 Special precautions for user : Not dangerous goods
14.7 Transport in bulk : Not dangerous goods
according to Annex II of
MARPOL 73/78 and the IBC
Code

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
according to Detergents : 30 % and more: Anionic surfactants
Regulation EC 648/2004 Other constituents: Perfumes

Seveso III: Directive : Not applicable.
2012/18/EU of the European
Parliament and of the Council
on the control of major-
accident hazards involving
dangerous substances.

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)
Regulations.
The Control of Substances Hazardous to Health Regulations.
Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Skin irritation 2, H315	Calculation method
Serious eye damage 1, H318	Calculation method
Chronic aquatic toxicity 3, H412	Calculation method

Full text of H-Statements

H290 May be corrosive to metals.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Floor cleaner - Manual process, without PPE

Life Cycle Stage : Widespread use by professional workers

LIQUIDSENSE QUARRY TILE FLOOR CLEANER

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8