

SAFETY DATA SHEET

Page 1 of 2

E1 EASY - FLOOR POLISH Data Sheet No. E1/WH

Revision 0
Revision date

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name E1 EASY - FLOOR POLISH
Data Sheet No. E1/WH

Company Winterhalter Limited
Winterhalter House
Roebuck Way
Knowlhill
Milton Keynes
MK5 8WH

2 HAZARDS IDENTIFICATION.

Main hazards No Significant Hazard

3 . COMPOSITION / INFORMATION ON INGREDIENTS.

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Mono ethylene glycol (Ethane-1,2-diol vapour)	1-10%	107-21-1	203-473-3	Xn; R22
Ethylene glycol monobutyl ether (2-Butoxyethanol)	0-0.5%	111-76-2	203-905-0	Xn; R20/21/22 Xi; R36/38

4. FIRST AID MEASURES

Skin contact May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Ingestion May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

Extinguishing media Use extinguishing media appropriate to the surrounding fire conditions.

Fire hazards Burning produces irritating, toxic and obnoxious fumes.

Protective equipment Wear suitable respiratory equipment when necessary.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions Do not allow product to enter drains. Prevent further spillage if safe.

Clean up methods Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.

Storage Keep containers tightly closed. Store in correctly labelled containers.

E1 EASY - FLOOR POLISH

Data Sheet No. E1/WH

Revision 0
Revision date

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Mono ethylene glycol (Ethane-1,2-diol vapour)	WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: 40	WEL 8-hr limit mg/m3: 52 WEL 15 min limit mg/m3: 104
Mono ethylene glycol (Ethane-1,2-diol particulate)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: -
Ethylene glycol monobutyl ether (2-Butoxyethanol)	WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: -

Hand protection Chemical resistant gloves (PVC)

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	White.
Odour	Characteristic.
Boiling point	100°C

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	Heat. Direct sunlight. Do NOT allow to freeze.

11. TOXICOLOGICAL INFORMATION

Toxicological information	No Significant Hazard.
----------------------------------	------------------------

12. ECOLOGICAL INFORMATION

Further information	Do not flush into surface water.
----------------------------	----------------------------------

13. DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
----------------------------	---

14. TRANSPORT INFORMATION

Further information	The product is not classified as dangerous for carriage.
----------------------------	--

15. REGULATORY INFORMATION

Risk phrases	NSH - No Significant Hazard.
---------------------	------------------------------

16. OTHER INFORMATION

Text of risk phrases in Section 3.	R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed. R22 - Harmful if swallowed. R36/38 - Irritating to eyes and skin.
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.