



SAFETY DATA SHEET DESTAINING POWDER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	DESTAINING POWDER
Product number	FHSB19
Internal identification	CL1062

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Detergent. For professional use only.
Uses advised against	Not for direct contact with Food or Beverage stuffs. Not for oral consumption. Not for use by hand.

1.3. Details of the supplier of the safety data sheet

Supplier	Bunzl UK & Ireland (UK) PrimeSource, PO BOX 15247, Birmingham, B23 3HN, UK - Tel: +44 (0) 8085 749 312 (IE) PrimeSource, Unit D9, Horizon Logistics Park, Swords, Co.Dublin, K67 N4T2, Ireland - Tel: +353 (0)1 630 1800
----------	---

Cleanline® is a registered trademark of Bunzl UK Ltd
info@prime-source.co.uk

1.4. Emergency telephone number

Emergency telephone	24 Hour Emergency Telephone Number +44 (0)1865 407 333. UK Environment Agency 24hour Advisory Service 0800 807060. This product is registered with the NPIS. Ireland - For information or to report a poisoning incident contact The National Poisons Information Centre (01 8092166). Irish Environmental Protection Agency 1890 335599 (This is a Lo Call Number)
---------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards	Met. Corr. 1 - H290
Health hazards	Skin Corr. 1B - H314 Eye Dam. 1 - H318
Environmental hazards	Not Classified

2.2. Label elements

Hazard pictograms



Signal word	Danger
Hazard statements	H314 Causes severe skin burns and eye damage. H290 May be corrosive to metals.

DESTAINING POWDER

Precautionary statements	P234 Keep only in original packaging. P280 Wear protective clothing, gloves, eye and face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P313 Get medical advice/ attention.
---------------------------------	---

Contains	SODIUM PERCARBONATE PEROXYHYDRATE, DISODIUM METASILICATE
-----------------	--

Detergent labelling	15 - < 30% phosphates, 5 - < 15% oxygen-based bleaching agents, < 5% non-ionic surfactants
----------------------------	--

Supplementary precautionary statements	P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.
---	--

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB. Note:- H290 Corrosive to Metals Statement relates to Damp Powder or Very Concentrated Solutions. The product is not corrosive to stainless steels at normal use strengths. This product will be very corrosive to soft metals such as Aluminium.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SODIUM CARBONATE CAS number: 497-19-8 EC number: 207-838-8	50-80%
Classification Eye Irrit. 2 - H319	
TRISODIUM PHOSPHATE CAS number: 7601-54-9 EC number: 231-509-8	10 - 15%
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335	
SODIUM PERCARBONATE PEROXYHYDRATE CAS number: 15630-89-4 EC number: 239-707-6	10-30%
Classification Ox. Liq. 2 - H272 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318	

DESTAINING POWDER

DISODIUM METASILICATE		5 - 10%
CAS number: 6834-92-0	EC number: 229-912-9	
Classification		
Met. Corr. 1 - H290		
Skin Corr. 1B - H314		
Eye Dam. 1 - H318		
STOT SE 3 - H335		

The full text for all hazard statements is displayed in Section 16.

Composition comments To the best of our knowledge, all of the substances used in this product are being supported for the relevant application in REACH. Note:- H290 Corrosive to Metals Statement relates to Damp Powder or Very Concentrated Solutions. The product is not corrosive at normal use strengths

SECTION 4: First aid measures

4.1. Description of first aid measures

General information When it is safe to do so, remove victim immediately from source of exposure. However, consideration should be given as to whether moving the victim will cause further injury. For immediate First Aid advice in the UK, dial 111.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Place unconscious person on the side in the recovery position and ensure breathing can take place. Get medical attention.

Skin contact Remove contaminated clothing that is not stuck to the skin. Flush area with clean water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information Neat product may cause chemical burns and permanent eye damage. Dilute product may cause irritation to the skin and eyes.

Inhalation Inhalation of dry dust may result in soreness of throat and in extreme cases burning.

Ingestion Unlikely route of exposure without deliberate abuse. If neat chemical is ingested, chemical burning of mouth, throat and GI tract will occur. If dilute chemical is ingested some soreness of the mouth, throat and GI tract may occur.

Skin contact May cause serious chemical burns to the skin. Use solutions may cause mild irritation, especially to open cuts and abrasions.

Eye contact May cause abrasion to the eye surface. Causes burns. May result in permanent eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Check for abrasion to the surface of eyes. Rinse well with water to neutral pH.

SECTION 5: Firefighting measures

5.1. Extinguishing media

DESTAINING POWDER

Suitable extinguishing media The product is non-combustible. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards This product is non combustible, on heating corrosive vapours may be formed.

5.3. Advice for firefighters

Protective actions during firefighting Protective clothing and respiratory protection should be worn when tackling fires involving this product. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Avoid or minimise the creation of any environmental contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections See sections 8,12 & 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Read and follow manufacturer's recommendations.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Store between 5 and 30 Degrees C.

7.3. Specific end use(s)

Specific end use(s) Detergent, refer to Product Information Sheet for full details.

Usage description This product is suitable for use in food preparation areas, but is not designed for direct food contact.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

DESTAINING POWDER

Ingredient comments

Where an exposure level is quoted, a risk assessment should consider if there is a need to monitor the atmosphere of the working environment. Results should be compared against the WEL and/or DNEL information provided. The Long Term WEL refers to total exposure of a worker to a specific substance averaged out over an 8 hour period.

The Short Term WEL refers to a single exposure of a worker to a specific substance over a 15 minute period.

If the Short Term WEL is exceeded and no Long Term Limit is set, further exposure during the working shift is not permitted. Further controls should be implemented to ensure that future exposure to the substance is reduced below the levels set before the activity is repeated/continued. Where no Short Term WEL exists, guidance from the HSE is to use a value of three times the Long Term WEL.

The WEL limits are laid down in the EH40 list as supplied by the HSE. Where a worker is exposed to levels approaching a limit, further exposure control measures should be considered to reduce exposure to the substance. Where new information becomes available under REACH, this will be passed on as revisions to the Safety Data Sheet.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

If use of this product generates dust, mists, vapours or fumes, process enclosures or local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits quoted in this msds or other data sources.

Personal protection

The PPE indicated above is not a COSHH assessment. It represents PPE that should be considered during the manufacture, distribution, use and final disposal stages of this product's life cycle. It is the responsibility of employers to conduct a COSHH/risk assessment to determine appropriate PPE levels. The information given below should be used to support this assessment. Where possible replace manual processes with automated or closed processes to minimise contact with the product.

Eye/face protection

If risk of splashing, wear safety goggles or face shield. Refer to EN Standard 166 to select appropriate level of protection.

Hand protection

Rubber (natural, latex). Neoprene. Polyvinyl chloride (PVC). The expected use of this product is such that gloves with a breakthrough time of >60 minutes should be regarded as sufficient. Gloves should be inspected regularly for damage and replaced when necessary. Refer to Standard EN 374 and EN 16523

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible. Reference to EN 13832 and EN 943 is useful when selecting footwear and clothing.

Hygiene measures

Not applicable.

Respiratory protection

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Workplace Exposure Limit. In the case of dust or aerosol formation (eg spraying), or vapour from hot vessels, use respiratory protection with an approved filter (P2).

Environmental exposure controls

Do not allow the substance to contaminate surface water/ground water. See points 6, 12 & 13.

General Health and Safety Measures.

Use solutions will have extreme pH and should be considered corrosive to skin. Use of gloves and eye protection is recommended. A full Risk Assessment should be carried out before handling any chemical(s). Risk Assessments should refer to COSHH, and any other relevant legislation or industry specific guidelines governing the use of chemicals.

DESTAINING POWDER

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Dusty powder.
Colour	White / off-white.
Odour	No characteristic odour.
Odour threshold	Not applicable.
pH	pH (diluted solution): 12.5 - 13.5 @ 1% w/v
Melting point	Not applicable.
Initial boiling point and range	Not applicable.
Flash point	Not available. Not applicable. Contains no Flammable Components
Evaporation rate	Not applicable.
Evaporation factor	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Bulk density	Not applicable.
Solubility(ies)	Soluble in water.
Partition coefficient	Not applicable. Not technically practical for mixtures.
Auto-ignition temperature	Not applicable.
Decomposition Temperature	Not applicable.
Viscosity	Not determined.
Explosive properties	Not applicable.
Explosive under the influence of a flame	Not considered to be explosive.

9.2. Other information

Refractive index	Not applicable.
Particle size	Not applicable.
Molecular weight	Not applicable.
Volatility	Not applicable.
Saturation concentration	Not applicable.
Critical temperature	Not applicable.
Volatile organic compound	Not applicable.
Explosive Properties	Not Classified as Explosive
Storage Temperature Range	0 to +40 Degrees C

DESTAINING POWDER

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Not expected to react when correctly stored and used. Mixing with other chemicals may produce unexpected reactions.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. - See note 10.6.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Refer to section 10.1.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong reducing agents. Strong oxidising agents. Reaction with Aluminium, Zinc, Tin, Copper or their alloys produces flammable Hydrogen Gas. Note:- Comment refers to neat product.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. - See section 10.5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 5,000.0

Carcinogenicity

Carcinogenicity The components of this formulation will not be systemically available in the body under normal conditions of handling. As a consequence it is not expected to cause cancer.

Reproductive toxicity

Reproductive toxicity - fertility The components of this formulation will not be systemically available in the body under normal conditions of use and handling. As a consequence it is not expected to be toxic to the reproductive system or developing foetus.

Inhalation - See section 4.2. Inhalation of dusts may result in soreness of throat, and in extreme cases burning may occur.

Ingestion May cause chemical burns in mouth, oesophagus and stomach.

Skin contact Prolonged contact with moist or wet product may cause burns.

Eye contact Risk of serious damage to eyes. May cause permanent eye injury.

SECTION 12: Ecological information

Ecotoxicity This product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.1. Toxicity

Acute aquatic toxicity

DESTAINING POWDER

Acute toxicity - fish Normal use of diluted product is unlikely to pose a risk.

12.2. Persistence and degradability

Persistence and degradability This product complies with the biodegradability criteria as laid down in the European Detergents Regulation No 648/2004 as amended.

12.3. Bioaccumulative potential

Bioaccumulative potential Not expected to bioaccumulate.

Partition coefficient Not applicable. Not technically practical for mixtures.

12.4. Mobility in soil

Mobility The product contains substances which are water soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3262

UN No. (IMDG) 3262

UN No. (ICAO) 3262

14.2. UN proper shipping name

Proper shipping name (ADR/RID) CORROSIVE SOLID,BASIC INORGANIC, N.O.S (DISODIUM TRIOXOSILICATE)

Proper shipping name (IMDG) CORROSIVE SOLID,BASIC INORGANIC, N.O.S (DISODIUM TRIOXOSILICATE)

Proper shipping name (ICAO) CORROSIVE SOLID,BASIC INORGANIC, N.O.S (DISODIUM TRIOXOSILICATE)

Proper shipping name (ADN) CORROSIVE SOLID,BASIC INORGANIC, N.O.S (DISODIUM TRIOXOSILICATE)

14.3. Transport hazard class(es)

ADR/RID class 8

ADR/RID label 8

IMDG class 8

ICAO class/division 8

DESTAINING POWDER

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-A, S-B

Hazard Identification Number 80
(ADR/RID)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations UK Adoption and Implementation of the UN Globally Harmonised System (GHS) on Classification and Labelling of Chemicals (GB CLP) and considers UK National REACH legislation.

EU legislation European Regulation (EC) No 1272/2008 (as amended) on Classification, Labelling and Packaging of Substances and Mixtures.
Also considered is the REACH Regulation (EC) No.1907/2006 (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet (EC) No. 1272/2008 : EU Regulation on Classification, Labelling and Packaging of Substances and Mixtures.
NPIS - National Poisons Information Service.
vPvB - Very Persistent, Very bioaccumulative.
PBT - Persistent, Bioaccumulative & Toxic.
REACH - Registration, Evaluation, Authorisation & restriction of CHemicals (Regulation EC 1907/2006).
DNEL - Derived No Effect Limit.
PNEC - Predicted No Effect Concentration.
COSHH - Control of Substances Hazardous to Health.
Industry - Refers in section 8 to application of the substance in an industrial process.
Professional - Refers in section 8 to application/use of the preparation/product in a skilled trade premises.

DESTAINING POWDER

General information	This document is a Safety Data Sheet, NOT a CoSHH assessment. It is the customer's responsibility to conduct a full CoSHH assessment, taking into account the information held within this document along with other local factors considered in a risk assessment. The Risk and Hazard statements listed below are the full text of abbreviations used in this document. They are not the final classification, for this refer to section 2.
Revision comments	Amendment to the emergency phone number in Section 1.4.
Revision date	02/02/2022
SDS number	11919
Hazard statements in full	H272 May intensify fire; oxidiser. H290 May be corrosive to metals. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation.
REACH extended MSDS comments	REACH requires that persons handling chemicals should take the necessary risk management measures, in accordance with assessments from manufacturers and importers of chemical substances. The relevant recommendations must be passed along the supply chain. These assessments are generally reported in Exposure Scenarios. Where Exposure Scenarios have been provided for substances used in this product, the relevant information is incorporated into the safety data sheet.
END OF SAFETY DATA SHEET	

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.